

# Amazon-Web-Services

## Exam Questions DOP-C02

AWS Certified DevOps Engineer - Professional



### NEW QUESTION 1

A company runs applications in AWS accounts that are in an organization in AWS Organizations. The applications use Amazon EC2 instances and Amazon S3. The company wants to detect potentially compromised EC2 instances, suspicious network activity, and unusual API activity in its existing AWS accounts and in any AWS accounts that the company creates in the future. When the company detects one of these events, the company wants to use an existing Amazon Simple Notification Service (Amazon SNS) topic to send a notification to its operational support team for investigation and remediation. Which solution will meet these requirements in accordance with AWS best practices?

- A. In the organization's management account, configure an AWS account as the Amazon GuardDuty administrator account.
- B. In the GuardDuty administrator account, add the company's existing AWS accounts to GuardDuty as members. In the GuardDuty administrator account, create an Amazon EventBridge rule with an event pattern to match GuardDuty events and to forward matching events to the SNS topic.
- C. In the organization's management account, configure Amazon GuardDuty to add newly created AWS accounts by invitation and to send invitations to the existing AWS accounts. Create an AWS CloudFormation stack set that accepts the GuardDuty invitation and creates an Amazon EventBridge rule. Configure the rule with an event pattern to match GuardDuty events and to forward matching events to the SNS topic.
- D. GuardDuty events and to forward matching events to the SNS topic.
- E. Configure the CloudFormation stack set to deploy into all AWS accounts in the organization.
- F. In the organization's management account, create an AWS CloudTrail organization trail. Activate the organization trail in all AWS accounts in the organization.
- G. Create an SCP that enables VPC Flow Logs in each account in the organization.
- H. Configure AWS Security Hub for the organization. Create an Amazon EventBridge rule with an event pattern to match Security Hub events and to forward matching events to the SNS topic.
- I. In the organization's management account, configure an AWS account as the AWS CloudTrail administrator account. In the CloudTrail administrator account, create a CloudTrail organization trail.
- J. Add the company's existing AWS accounts to the organization trail. Create an SCP that enables VPC Flow Logs in each account in the organization.
- K. Configure AWS Security Hub for the organization.
- L. Create an Amazon EventBridge rule with an event pattern to match Security Hub events and to forward matching events to the SNS topic.

**Answer: B**

#### Explanation:

It allows the company to detect potentially compromised EC2 instances, suspicious network activity, and unusual API activity in its existing AWS accounts and in any AWS accounts that the company creates in the future using Amazon GuardDuty. It also provides a solution for automatically adding future AWS accounts to GuardDuty by configuring GuardDuty to add newly created AWS accounts by invitation and to send invitations to the existing AWS accounts.

### NEW QUESTION 2

A DevOps engineer needs to apply a core set of security controls to an existing set of AWS accounts. The accounts are in an organization in AWS Organizations. Individual teams will administer individual accounts by using the AdministratorAccess AWS managed policy. For all accounts, AWS CloudTrail and AWS Config must be turned on in all available AWS Regions. Individual account administrators must not be able to edit or delete any of the baseline resources. However, individual account administrators must be able to edit or delete their own CloudTrail trails and AWS Config rules. Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create an AWS CloudFormation template that defines the standard account resource.
- B. Deploy the template to all accounts from the organization's management account by using CloudFormation StackSet.
- C. Set the stack policy to deny Update/Delete actions.
- D. Enable AWS Control Tower.
- E. Enroll the existing accounts in AWS Control Tower.
- F. Grant the individual account administrators access to CloudTrail and AWS Config.
- G. Designate an AWS Config management account.
- H. Create AWS Config recorders in all accounts by using AWS CloudFormation StackSet.
- I. Deploy AWS Config rules to the organization by using the AWS Config management account.
- J. Create a CloudTrail organization trail in the organization's management account.
- K. Deny modification or deletion of the AWS Config recorders by using an SCP.
- L. Create an AWS CloudFormation template that defines the standard account resource.
- M. Deploy the template to all accounts from the organization's management account by using CloudFormation StackSets. Create an SCP that prevents updates or deletions to CloudTrail resources or AWS Config resources unless the principal is an administrator of the organization's management account.

**Answer: D**

### NEW QUESTION 3

A DevOps engineer is designing an application that integrates with a legacy REST API. The application has an AWS Lambda function that reads records from an Amazon Kinesis data stream. The Lambda function sends the records to the legacy REST API.

Approximately 10% of the records that the Lambda function sends from the Kinesis data stream have data errors and must be processed manually. The Lambda function event source configuration has an Amazon Simple Queue Service (Amazon SQS) dead-letter queue as an on-failure destination. The DevOps engineer has configured the Lambda function to process records in batches and has implemented retries in case of failure.

During testing, the DevOps engineer notices that the dead-letter queue contains many records that have no data errors and that already have been processed by the legacy REST API. The DevOps engineer needs to configure the Lambda function's event source options to reduce the number of errorless records that are sent to the dead-letter queue.

Which solution will meet these requirements?

- A. Increase the retry attempts.
- B. Configure the setting to split the batch when an error occurs.
- C. Increase the concurrent batches per shard.
- D. Decrease the maximum age of record.

**Answer: B**

#### Explanation:

This solution will meet the requirements because it will reduce the number of errorless records that are sent to the dead-letter queue. When you configure the setting to split the batch when an error occurs, Lambda will retry only the records that caused the error, instead of retrying the entire batch. This way, the records that have no data errors and have already been processed by the legacy REST API will not be retried and sent to the dead-letter queue unnecessarily.

<https://docs.aws.amazon.com/lambda/latest/dg/with-kinesis.html>

#### NEW QUESTION 4

A company uses Amazon S3 to store proprietary information. The development team creates buckets for new projects on a daily basis. The security team wants to ensure that all existing and future buckets have encryption logging and versioning enabled. Additionally, no buckets should ever be publicly read or write accessible.

What should a DevOps engineer do to meet these requirements?

- A. Enable AWS CloudTrail and configure automatic remediation using AWS Lambda.
- B. Enable AWS Config rules and configure automatic remediation using AWS Systems Manager documents.
- C. Enable AWS Trusted Advisor and configure automatic remediation using Amazon EventBridge.
- D. Enable AWS Systems Manager and configure automatic remediation using Systems Manager documents.

**Answer: B**

#### Explanation:

<https://aws.amazon.com/blogs/mt/aws-config-auto-remediation-s3-compliance/> <https://aws.amazon.com/blogs/aws/aws-config-rules-dynamic-compliance-checking-for-cloud-resources/>

#### NEW QUESTION 5

A company is implementing a well-architected design for its globally accessible API stack. The design needs to ensure both high reliability and fast response times for users located in North America and Europe.

The API stack contains the following three tiers: Amazon API Gateway  
AWS Lambda Amazon DynamoDB

Which solution will meet the requirements?

- A. Configure Amazon Route 53 to point to API Gateway APIs in North America and Europe using health check
- B. Configure the APIs to forward requests to a Lambda function in that Region
- C. Configure the Lambda functions to retrieve and update the data in a DynamoDB table in the same Region as the Lambda function.
- D. Configure Amazon Route 53 to point to API Gateway APIs in North America and Europe using latency-based routing and health check
- E. Configure the APIs to forward requests to a Lambda function in that Region
- F. Configure the Lambda functions to retrieve and update the data in a DynamoDB global table.
- G. Configure Amazon Route 53 to point to API Gateway in North America, create a disaster recovery API in Europe, and configure both APIs to forward requests to the Lambda functions in that Region
- H. Retrieve the data from a DynamoDB global table
- I. Deploy a Lambda function to check the North America API health every 5 minutes
- J. In the event of a failure, update Route 53 to point to the disaster recovery API.
- K. Configure Amazon Route 53 to point to API Gateway API in North America using latency-based routing
- L. Configure the API to forward requests to the Lambda function in the Region nearest to the user
- M. Configure the Lambda function to retrieve and update the data in a DynamoDB table.

**Answer: B**

#### NEW QUESTION 6

A company has a mobile application that makes HTTP API calls to an Application Load Balancer (ALB). The ALB routes requests to an AWS Lambda function. Many different versions of the application are in use at any given time, including versions that are in testing by a subset of users. The version of the application is defined in the user-agent header that is sent with all requests to the API.

After a series of recent changes to the API, the company has observed issues with the application. The company needs to gather a metric for each API operation by response code for each version of the application that is in use. A DevOps engineer has modified the Lambda function to extract the API operation name, version information from the user-agent header and response code.

Which additional set of actions should the DevOps engineer take to gather the required metrics?

- A. Modify the Lambda function to write the API operation name, response code, and version number as a log line to an Amazon CloudWatch Logs log group
- B. Configure a CloudWatch Logs metric filter that increments a metric for each API operation name
- C. Specify response code and application version as dimensions for the metric.
- D. Modify the Lambda function to write the API operation name, response code, and version number as a log line to an Amazon CloudWatch Logs log group
- E. Configure a CloudWatch Logs Insights query to populate CloudWatch metrics from the log line
- F. Specify response code and application version as dimensions for the metric.
- G. Configure the ALB access logs to write to an Amazon CloudWatch Logs log group
- H. Modify the Lambda function to respond to the ALB with the API operation name, response code, and version number as response metadata
- I. Configure a CloudWatch Logs metric filter that increments a metric for each API operation name
- J. Specify response code and application version as dimensions for the metric.
- K. Configure AWS X-Ray integration on the Lambda function
- L. Modify the Lambda function to create an X-Ray subsegment with the API operation name, response code, and version number
- M. Configure X-Ray insights to extract an aggregated metric for each API operation name and to publish the metric to Amazon CloudWatch
- N. Specify response code and application version as dimensions for the metric.

**Answer: A**

#### Explanation:

"Note that the metric filter is different from a log insights query, where the experience is interactive and provides immediate search results for the user to investigate.

No automatic action can be invoked from an insights query. Metric filters, on the other hand, will generate metric data in the form of a time series. This lets you create alarms that integrate into your ITSM processes, execute AWS Lambda functions, or even create anomaly detection models."

<https://aws.amazon.com/blogs/mt/quantify-custom-application-metrics-with-amazon-cloudwatch-logs-and-metric-filters/>

#### NEW QUESTION 7

A DevOps engineer has automated a web service deployment by using AWS CodePipeline with the following steps:

- 1) An AWS CodeBuild project compiles the deployment artifact and runs unit tests.

2) An AWS CodeDeploy deployment group deploys the web service to Amazon EC2 instances in the staging environment.  
3) A CodeDeploy deployment group deploys the web service to EC2 instances in the production environment.  
The quality assurance (QA) team requests permission to inspect the build artifact before the deployment to the production environment occurs. The QA team wants to run an internal penetration testing tool to conduct manual tests. The tool will be invoked by a REST API call.  
Which combination of actions should the DevOps engineer take to fulfill this request? (Choose two.)

- A. Insert a manual approval action between the test actions and deployment actions of the pipeline.
- B. Modify the buildspec.yml file for the compilation stage to require manual approval before completion.
- C. Update the CodeDeploy deployment groups so that they require manual approval to proceed.
- D. Update the pipeline to directly call the REST API for the penetration testing tool.
- E. Update the pipeline to invoke an AWS Lambda function that calls the REST API for the penetration testing tool.

**Answer:** AE

#### NEW QUESTION 8

A company uses AWS CodePipeline pipelines to automate releases of its application. A typical pipeline consists of three stages: build, test, and deployment. The company has been using a separate AWS CodeBuild project to run scripts for each stage. However, the company now wants to use AWS CodeDeploy to handle the deployment stage of the pipelines.

The company has packaged the application as an RPM package and must deploy the application to a fleet of Amazon EC2 instances. The EC2 instances are in an EC2 Auto Scaling group and are launched from a common AMI.

Which combination of steps should a DevOps engineer perform to meet these requirements? (Choose two.)

- A. Create a new version of the common AMI with the CodeDeploy agent installed.
- B. Update the IAM role of the EC2 instances to allow access to CodeDeploy.
- C. Create a new version of the common AMI with the CodeDeploy agent installed.
- D. Create an AppSpec file that contains application deployment scripts and grants access to CodeDeploy.
- E. Create an application in CodeDeploy.
- F. Configure an in-place deployment type.
- G. Specify the Auto Scaling group as the deployment target.
- H. Add a step to the CodePipeline pipeline to use EC2 Image Builder to create a new AMI.
- I. Configure CodeDeploy to deploy the newly created AMI.
- J. Create an application in CodeDeploy.
- K. Configure an in-place deployment type.
- L. Specify the Auto Scaling group as the deployment target.
- M. Update the CodePipeline pipeline to use the CodeDeploy action to deploy the application.
- N. Create an application in CodeDeploy.
- O. Configure an in-place deployment type.
- P. Specify the EC2 instances that are launched from the common AMI as the deployment target.
- Q. Update the CodePipeline pipeline to use the CodeDeploy action to deploy the application.

**Answer:** AD

#### Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/integrations-aws-auto-scaling.html>

#### NEW QUESTION 9

A company's developers use Amazon EC2 instances as remote workstations. The company is concerned that users can create or modify EC2 security groups to allow unrestricted inbound access.

A DevOps engineer needs to develop a solution to detect when users create unrestricted security group rules. The solution must detect changes to security group rules in near real time, remove unrestricted rules, and send email notifications to the security team. The DevOps engineer has created an AWS Lambda function that checks for security group ID from input, removes rules that grant unrestricted access, and sends notifications through Amazon Simple Notification Service (Amazon SNS).

What should the DevOps engineer do next to meet the requirements?

- A. Configure the Lambda function to be invoked by the SNS topic.
- B. Create an AWS CloudTrail subscription for the SNS topic.
- C. Configure a subscription filter for security group modification events.
- D. Create an Amazon EventBridge scheduled rule to invoke the Lambda function.
- E. Define a schedule pattern that runs the Lambda function every hour.
- F. Create an Amazon EventBridge event rule that has the default event bus as the source.
- G. Define the rule's event pattern to match EC2 security group creation and modification events.
- H. Configure the rule to invoke the Lambda function.
- I. Create an Amazon EventBridge custom event bus that subscribes to events from all AWS services.
- J. Configure the Lambda function to be invoked by the custom event bus.

**Answer:** C

#### Explanation:

To meet the requirements, the DevOps engineer should create an Amazon EventBridge event rule that has the default event bus as the source. The rule's event pattern should match EC2 security group creation and modification events, and it should be configured to invoke the Lambda function. This solution will allow for near real-time detection of security group rule changes and will trigger the Lambda function to remove any unrestricted rules and send email notifications to the security team. <https://repost.aws/knowledge-center/monitor-security-group-changes-ec2>

#### NEW QUESTION 10

A company has multiple member accounts that are part of an organization in AWS Organizations. The security team needs to review every Amazon EC2 security group and their inbound and outbound rules. The security team wants to programmatically retrieve this information from the member accounts using an AWS Lambda function in the management account of the organization.

Which combination of access changes will meet these requirements? (Choose three.)

- A. Create a trust relationship that allows users in the member accounts to assume the management account IAM role.

- B. Create a trust relationship that allows users in the management account to assume the IAM roles of the member accounts.
- C. Create an IAM role in each member account that has access to the AmazonEC2ReadOnlyAccess managed policy.
- D. Create an IAM role in each member account to allow the sts:AssumeRole action against the management account IAM role's ARN.
- E. Create an IAM role in the management account that allows the sts:AssumeRole action against the member account IAM role's ARN.
- F. Create an IAM role in the management account that has access to the AmazonEC2ReadOnlyAccess managed policy.

**Answer:** BCE

**Explanation:**

<https://aws.amazon.com/premiumsupport/knowledge-center/lambda-function-assume-iam-role/> <https://kreuzwerker.de/post/aws-multi-account-setups-reloaded>

**NEW QUESTION 10**

A company is launching an application. The application must use only approved AWS services. The account that runs the application was created less than 1 year ago and is assigned to an AWS Organizations OU.

The company needs to create a new Organizations account structure. The account structure must have an appropriate SCP that supports the use of only services that are currently active in the AWS account.

The company will use AWS Identity and Access Management (IAM) Access Analyzer in the solution.

Which solution will meet these requirements?

- A. Create an SCP that allows the services that IAM Access Analyzer identifies
- B. Create an OU for the account
- C. Move the account into the new OU
- D. Attach the new SCP to the new OU
- E. Detach the default FullAWSAccess SCP from the new OU.
- F. Create an SCP that denies the services that IAM Access Analyzer identifies
- G. Create an OU for the account
- H. Move the account into the new OU
- I. Attach the new SCP to the new OU.
- J. Create an SCP that allows the services that IAM Access Analyzer identifies
- K. Attach the new SCP to the organization's root.
- L. Create an SCP that allows the services that IAM Access Analyzer identifies
- M. Create an OU for the account
- N. Move the account into the new OU
- O. Attach the new SCP to the management account
- P. Detach the default FullAWSAccess SCP from the new OU.

**Answer:** A

**Explanation:**

To meet the requirements of creating a new Organizations account structure with an appropriate SCP that supports the use of only services that are currently active in the AWS account, the company should use the following solution:

? Create an SCP that allows the services that IAM Access Analyzer identifies. IAM Access Analyzer is a service that helps identify potential resource-access risks by analyzing resource-based policies in the AWS environment. IAM Access Analyzer can also generate IAM policies based on access activity in the AWS CloudTrail logs. By using IAM Access Analyzer, the company can create an SCP that grants only the permissions that are required for the application to run, and denies all other services. This way, the company can enforce the use of only approved AWS services and reduce the risk of unauthorized access<sup>12</sup>

? Create an OU for the account. Move the account into the new OU. An OU is a container for accounts within an organization that enables you to group accounts that have similar business or security requirements. By creating an OU for the account, the company can apply policies and manage settings for the account as a group. The company should move the account into the new OU to make it subject to the policies attached to the OU<sup>3</sup>

? Attach the new SCP to the new OU. Detach the default FullAWSAccess SCP from the new OU. An SCP is a type of policy that specifies the maximum permissions for an organization or organizational unit (OU). By attaching the new SCP to the new OU, the company can restrict the services that are available to all accounts in that OU, including the account that runs the application. The company should also detach the default FullAWSAccess SCP from the new OU, because this policy allows all actions on all AWS services and might override or conflict with the new SCP<sup>45</sup>

The other options are not correct because they do not meet the requirements or follow best practices. Creating an SCP that denies the services that IAM Access Analyzer identifies is not a good option because it might not cover all possible services that are not approved or required for the application. A deny policy is also more difficult to maintain and update than an allow policy. Creating an SCP that allows the services that IAM Access Analyzer identifies and attaching it to the organization's root is not a good option because it might affect other accounts and OUs in the organization that have different service requirements or approvals. Creating an SCP that allows the services that IAM Access Analyzer identifies and attaching it to the management account is not a valid option because SCPs cannot be attached directly to accounts, only to OUs or roots.

References:

- ? 1: Using AWS Identity and Access Management Access Analyzer - AWS Identity and Access Management
- ? 2: Generate a policy based on access activity - AWS Identity and Access Management
- ? 3: Organizing your accounts into OUs - AWS Organizations
- ? 4: Service control policies - AWS Organizations
- ? 5: How SCPs work - AWS Organizations

**NEW QUESTION 15**

A company sells products through an ecommerce web application The company wants a dashboard that shows a pie chart of product transaction details. The company wants to integrate the dashboard With the company's existing Amazon CloudWatch dashboards

Which solution Will meet these requirements With the MOST operational efficiency?

- A. Update the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction
- B. Use CloudWatch Logs Insights to query the log group and to visualize the results in a pie chart format Attach the results to the desired CloudWatch dashboard.
- C. Update the ecommerce application to emit a JSON object to an Amazon S3 bucket for each processed transaction
- D. Use Amazon Athena to query the S3 bucket and to visualize the results In a Pie chart format
- E. Export the results from Athena Attach the results to the desired CloudWatch dashboard
- F. Update the ecommerce application to use AWS X-Ray for instrumentation
- G. Create a new X-Ray subsegment Add an annotation for each processed transaction
- H. Use X-Ray traces to query the data and to visualize the results in a pie chart format Attach the results to the desired CloudWatch dashboard
- I. Update the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction\_ Create an AWS Lambda function to aggregate and write the results to Amazon DynamoDB
- J. Create a Lambda subscription filter for the log file

K. Attach the results to the desired CloudWatch dashboard.

**Answer:** A

**Explanation:**

The correct answer is A.

A comprehensive and detailed explanation is:

? Option A is correct because it meets the requirements with the most operational efficiency. Updating the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction is a simple and cost-effective way to collect the data needed for the dashboard. Using CloudWatch Logs Insights to query the log group and to visualize the results in a pie chart format is also a convenient and integrated solution that leverages the existing CloudWatch dashboards. Attaching the results to the desired CloudWatch dashboard is straightforward and does not require any additional steps or services.

? Option B is incorrect because it introduces unnecessary complexity and cost.

Updating the ecommerce application to emit a JSON object to an Amazon S3 bucket for each processed transaction is a valid way to store the data, but it requires creating and managing an S3 bucket and its permissions. Using Amazon Athena to query the S3 bucket and to visualize the results in a pie chart format is also a valid way to analyze the data, but it incurs charges based on the amount of data scanned by each query. Exporting the results from Athena and attaching them to the desired CloudWatch dashboard is also an extra step that adds more overhead and latency.

? Option C is incorrect because it uses AWS X-Ray for an inappropriate purpose.

Updating the ecommerce application to use AWS X-Ray for instrumentation is a good practice for monitoring and tracing distributed applications, but it is not designed for aggregating product transaction details. Creating a new X-Ray subsegment and adding an annotation for each processed transaction is possible, but it would clutter the X-Ray service map and make it harder to debug performance issues. Using X-Ray traces to query the data and to visualize the results in a pie chart format is also possible, but it would require custom code and logic that are not supported by X-Ray natively. Attaching the results to the desired CloudWatch dashboard is also not supported by X-Ray directly, and would require additional steps or services.

? Option D is incorrect because it introduces unnecessary complexity and cost.

Updating the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction is a simple and cost-effective way to collect the data needed for the dashboard, as in option A. However, creating an AWS Lambda function to aggregate and write the results to Amazon DynamoDB is redundant, as CloudWatch Logs Insights can already perform aggregation queries on log data. Creating a Lambda subscription filter for the log file is also redundant, as CloudWatch Logs Insights can already access log data directly. Attaching the results to the desired CloudWatch dashboard would also require additional steps or services, as DynamoDB does not support native integration with CloudWatch dashboards.

References:

? CloudWatch Logs Insights

? Amazon Athena

? AWS X-Ray

? AWS Lambda

? Amazon DynamoDB

**NEW QUESTION 17**

A company has multiple accounts in an organization in AWS Organizations. The company's SecOps team needs to receive an Amazon Simple Notification Service (Amazon SNS) notification if any account in the organization turns off the Block Public Access feature on an Amazon S3 bucket. A DevOps engineer must implement this change without affecting the operation of any AWS accounts. The implementation must ensure that individual member accounts in the organization cannot turn off the notification.

Which solution will meet these requirements?

- A. Designate an account to be the delegated Amazon GuardDuty administrator account
- B. Turn on GuardDuty for all accounts across the organization
- C. In the GuardDuty administrator account, create an SNS topic
- D. Subscribe the SecOps team's email address to the SNS topic
- E. In the same account, create an Amazon EventBridge rule that uses an event pattern for GuardDuty findings and a target of the SNS topic.
- F. Create an AWS CloudFormation template that creates an SNS topic and subscribes the SecOps team's email address to the SNS topic
- G. In the template, include an Amazon EventBridge rule that uses an event pattern of CloudTrail activity for s3:PutBucketPublicAccessBlock and a target of the SNS topic
- H. Deploy the stack to every account in the organization by using CloudFormation StackSets.
- I. Turn on AWS Config across the organization
- J. In the delegated administrator account, create an SNS topic
- K. Subscribe the SecOps team's email address to the SNS topic
- L. Deploy a conformance pack that uses the s3-bucket-level-public-access-prohibited AWS Config managed rule in each account and uses an AWS Systems Manager document to publish an event to the SNS topic to notify the SecOps team.
- M. Turn on Amazon Inspector across the organization
- N. In the Amazon Inspector delegated administrator account, create an SNS topic
- O. Subscribe the SecOps team's email address to the SNS topic
- P. In the same account, create an Amazon EventBridge rule that uses an event pattern for public network exposure of the S3 bucket and publishes an event to the SNS topic to notify the SecOps team.

**Answer:** C

**Explanation:**

Amazon GuardDuty is primarily on threat detection and response, not configuration monitoring. A conformance pack is a collection of AWS Config rules and remediation actions that can be easily deployed as a single entity in an account and a Region or across an organization in AWS Organizations.

<https://docs.aws.amazon.com/config/latest/developerguide/conformance-packs.html> <https://docs.aws.amazon.com/config/latest/developerguide/s3-account-level-public-access-blocks.html>

**NEW QUESTION 22**

A company deploys its corporate infrastructure on AWS across multiple AWS Regions and Availability Zones. The infrastructure is deployed on Amazon EC2 instances and connects with AWS IoT Greengrass devices. The company deploys additional resources on on-premises servers that are located in the corporate headquarters.

The company wants to reduce the overhead involved in maintaining and updating its resources. The company's DevOps team plans to use AWS Systems Manager to implement automated management and application of patches. The DevOps team confirms that Systems Manager is available in the Regions that the resources are deployed in. Systems Manager also is available in a Region near the corporate headquarters.

Which combination of steps must the DevOps team take to implement automated patch and configuration management across the company's EC2 instances, IoT devices, and on-premises infrastructure? (Select THREE.)

- A. Apply tags to all the EC2 instances
- B. AWS IoT Greengrass devices, and on-premises servers
- C. Use Systems Manager Session Manager to push patches to all the tagged devices.
- D. Use Systems Manager Run Command to schedule patching for the EC2 instances AWS IoT Greengrass devices and on-premises servers.
- E. Use Systems Manager Patch Manager to schedule patching IoT the EC2 instances AWS IoT Greengrass devices and on-premises servers as a Systems Manager maintenance window task.
- F. Configure Amazon EventBridge to monitor Systems Manager Patch Manager for updates to patch baseline
- G. Associate Systems Manager Run Command with the event to initiate a patch action for all EC2 instances AWS IoT Greengrass devices and on-premises servers.
- H. Create an IAM instance profile for Systems Manager Attach the instance profile to all the EC2 instances in the AWS account
- I. For the AWS IoT Greengrass devices and on-premises servers create an IAM service role for Systems Manager.
- J. Generate a managed-instance activation Use the Activation Code and Activation ID to install Systems Manager Agent (SSM Agent) on each server in the on-premises environment Update the AWS IoT Greengrass IAM token exchange role Use the role to deploy SSM Agent on all the IoT devices.

**Answer:** CEF

**Explanation:**

[https://aws.amazon.com/blogs/mt/how-to-centrally-manage-aws-iot-greengrass-devices-using-aws-systems-manager/?force\\_isolation=true](https://aws.amazon.com/blogs/mt/how-to-centrally-manage-aws-iot-greengrass-devices-using-aws-systems-manager/?force_isolation=true)

**NEW QUESTION 23**

A video-sharing company stores its videos in Amazon S3. The company has observed a sudden increase in video access requests, but the company does not know which videos are most popular. The company needs to identify the general access pattern for the video files. This pattern includes the number of users who access a certain file on a given day, as well as the number of users who access a certain file on a given day, as well as the number of users who access a certain file on a given day. A DevOps engineer manages a large commercial website that runs on Amazon EC2. The website uses Amazon Kinesis Data Streams to collect and process web logs. The DevOps engineer manages the Kinesis consumer application, which also runs on Amazon EC2. Sudden increases of data cause the Kinesis consumer application to fall behind and the Kinesis data streams drop records before the records can be processed. The DevOps engineer must implement a solution to improve stream handling. Which solution meets these requirements with the MOST operational efficiency? or of pull requests for certain files. How can the company meet these requirements with the LEAST amount of effort?

- A. Activate S3 server access logging
- B. Import the access logs into an Amazon Aurora database
- C. Use an Aurora SQL query to analyze the access patterns.
- D. Activate S3 server access logging
- E. Use Amazon Athena to create an external table with the log file
- F. Use Athena to create a SQL query to analyze the access patterns.
- G. Invoke an AWS Lambda function for every S3 object access event
- H. Configure the Lambda function to write the file access information, such as user, S3 bucket, and file key, to an Amazon Aurora database
- I. S3 bucket, and file key, to an Amazon Aurora database
- J. Use an Aurora SQL query to analyze the access patterns.
- K. Record an Amazon CloudWatch Logs log message for every S3 object access event
- L. Configure a CloudWatch Logs log stream to write the file access information, such as user, S3 bucket, and file key, to an Amazon Kinesis Data Analytics for SQL applications
- M. Perform a sliding window analysis.

**Answer:** B

**Explanation:**

Activating S3 server access logging and using Amazon Athena to create an external table with the log files is the easiest and most cost-effective way to analyze access patterns. This option requires minimal setup and allows for quick analysis of the access patterns with SQL queries. Additionally, Amazon Athena scales automatically to match the query load, so there is no need for additional infrastructure provisioning or management.

**NEW QUESTION 27**

A company has multiple AWS accounts. The company uses AWS IAM Identity Center (AWS Single Sign-On) that is integrated with AWS Toolkit for Microsoft Azure DevOps. The attributes for access control feature is enabled in IAM Identity Center.

The attribute mapping list contains two entries. The department key is mapped to `#{path:enterprise.department}`. The costCenter key is mapped to `#{path:enterprise.costCenter}`.

All existing Amazon EC2 instances have a department tag that corresponds to three company departments (d1, d2, d3). A DevOps engineer must create policies based on the matching attributes. The policies must minimize administrative effort and must grant each Azure AD user access to only the EC2 instances that are tagged with the user's respective department name.

Which condition key should the DevOps engineer include in the custom permissions policies to meet these requirements?

A.

```
"Condition": {
  "ForAllValues:StringEquals": {
    "aws:TagKeys": ["department"]
  }
}
```

B.

```
"Condition": {
  "StringEquals": {
    "aws:PrincipalTag/department": "$(aws:ResourceTag/department)"
  }
}
```

C.

```
"Condition": {
  "StringEquals": {
    "ec2:ResourceTag/department": "$(aws:PrincipalTag/department)"
  }
}
```

D.

```
"Condition": {
  "ForAllValues:StringEquals": {
    "ec2:ResourceTag/department": ["d1", "d2", "d3"]
  }
}
```

A.

**Answer: C**

**Explanation:**

<https://docs.aws.amazon.com/singlesignon/latest/userguide/configure-abac.html>

### NEW QUESTION 31

A DevOps team uses AWS CodePipeline, AWS CodeBuild, and AWS CodeDeploy to deploy an application. The application is a REST API that uses AWS Lambda functions and Amazon API Gateway. Recent deployments have introduced errors that have affected many customers. The DevOps team needs a solution that reverts to the most recent stable version of the application when an error is detected. The solution must affect the fewest customers possible. Which solution will meet these requirements with the MOST operational efficiency?

- A. Set the deployment configuration in CodeDeploy to LambdaAllAtOnce. Configure automatic rollbacks on the deployment group. Create an Amazon CloudWatch alarm that detects HTTP Bad Gateway errors on API Gateway. Configure the deployment group to roll back when the number of alarms meets the alarm threshold.
- B. Set the deployment configuration in CodeDeploy to LambdaCanary10Percent10Minute.
- C. Configure automatic rollbacks on the deployment group. Create an Amazon CloudWatch alarm that detects HTTP Bad Gateway errors on API Gateway. Configure the deployment group to roll back when the number of alarms meets the alarm threshold.
- D. Set the deployment configuration in CodeDeploy to LambdaAllAtOnce. Configure manual rollbacks on the deployment group.
- E. Create an Amazon Simple Notification Service (Amazon SNS) topic to send notifications every time a deployment fails.
- F. Configure the SNS topic to invoke a new Lambda function that stops the current deployment and starts the most recent successful deployment.
- G. Set the deployment configuration in CodeDeploy to LambdaCanary10Percent10Minutes. Configure manual rollbacks on the deployment group. Create a metric filter on an Amazon CloudWatch log group for API Gateway to monitor HTTP Bad Gateway errors.
- H. Configure the metric filter to invoke a new Lambda function that stops the current deployment and starts the most recent successful deployment.

**Answer: B**

**Explanation:**

? Option A is incorrect because setting the deployment configuration to LambdaAllAtOnce means that the new version of the application will be deployed to all Lambda functions at once, affecting all customers. This does not meet the requirement of affecting the fewest customers possible. Moreover, configuring automatic rollbacks on the deployment group is not operationally efficient, as it requires manual intervention to fix the errors and redeploy the application.

? Option B is correct because setting the deployment configuration to LambdaCanary10Percent10Minutes means that the new version of the application will be deployed to 10 percent of the Lambda functions first, and then to the remaining 90 percent after 10 minutes. This minimizes the impact of errors on customers, as only 10 percent of them will be affected by a faulty deployment. Configuring automatic rollbacks on the deployment group also meets the requirement of reverting to the most recent stable version of the application when an error is detected. Creating a CloudWatch alarm that detects HTTP Bad Gateway errors on API Gateway is a valid way to monitor the health of the application and trigger a rollback if needed.

? Option C is incorrect because setting the deployment configuration to LambdaAllAtOnce means that the new version of the application will be deployed to all Lambda functions at once, affecting all customers. This does not meet the requirement of affecting the fewest customers possible. Moreover, configuring manual rollbacks on the deployment group is not operationally efficient, as it requires human intervention to stop the current deployment and start a new one. Creating an SNS topic to send notifications every time a deployment fails is not sufficient to detect errors in the application, as it does not monitor the API Gateway responses.

? Option D is incorrect because configuring manual rollbacks on the deployment group is not operationally efficient, as it requires human intervention to stop the current deployment and start a new one. Creating a metric filter on a CloudWatch log group for API Gateway to monitor HTTP Bad Gateway errors is a valid way to monitor the health of the application, but invoking a new Lambda function to perform a rollback is unnecessary and complex, as CodeDeploy already provides automatic rollback functionality.

References:

- ? AWS CodeDeploy Deployment Configurations
- ? [AWS CodeDeploy Rollbacks]
- ? Amazon CloudWatch Alarms

#### NEW QUESTION 34

A company has migrated its container-based applications to Amazon EKS and want to establish automated email notifications. The notifications sent to each email address are for specific activities related to EKS components. The solution will include Amazon SNS topics and an AWS Lambda function to evaluate incoming log events and publish messages to the correct SNS topic.

Which logging solution will support these requirements?

- A. Enable Amazon CloudWatch Logs to log the EKS component
- B. Create a CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- C. Enable Amazon CloudWatch Logs to log the EKS component
- D. Create CloudWatch Logs Insights queries linked to Amazon EventBridge events that invoke Lambda.
- E. Enable Amazon S3 logging for the EKS component
- F. Configure an Amazon CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- G. Enable Amazon S3 logging for the EKS component
- H. Configure S3 PUT Object event notifications with AWS Lambda as the destination.

**Answer:** A

#### Explanation:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html#LambdaFunctionExample>  
<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html>

#### NEW QUESTION 35

A company's application development team uses Linux-based Amazon EC2 instances as bastion hosts. Inbound SSH access to the bastion hosts is restricted to specific IP addresses, as defined in the associated security groups. The company's security team wants to receive a notification if the security group rules are modified to allow SSH access from any IP address.

What should a DevOps engineer do to meet this requirement?

- A. Create an Amazon EventBridge rule with a source of aws.cloudtrail and the event name AuthorizeSecurityGroupIngress
- B. Define an Amazon Simple Notification Service (Amazon SNS) topic as the target.
- C. Enable Amazon GuardDuty and check the findings for security groups in AWS Security Hub
- D. Configure an Amazon EventBridge rule with a custom pattern that matches GuardDuty events with an output of NON\_COMPLIANT
- E. Define an Amazon Simple Notification Service (Amazon SNS) topic as the target.
- F. Create an AWS Config rule by using the restricted-ssh managed rule to check whether security groups disallow unrestricted incoming SSH traffic
- G. Configure automatic remediation to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.
- H. Enable Amazon Inspector
- I. Include the Common Vulnerabilities and Exposures-1.1 rules package to check the security groups that are associated with the bastion host
- J. Configure Amazon Inspector to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.

**Answer:** A

#### Explanation:

<https://aws.amazon.com/premiumsupport/knowledge-center/monitor-security-group-changes-ec2/>

#### NEW QUESTION 40

A DevOps team is merging code revisions for an application that uses an Amazon RDS Multi-AZ DB cluster for its production database. The DevOps team uses continuous integration to periodically verify that the application works. The DevOps team needs to test the changes before the changes are deployed to the production database.

Which solution will meet these requirements?

- A. Use a buildspec file in AWS CodeBuild to restore the DB cluster from a snapshot of the production database run integration tests, and drop the restored database after verification.
- B. Deploy the application to production
- C. Configure an audit log of data control language (DCL) operations to capture database activities to perform if verification fails.
- D. Create a snapshot of the DB cluster before deploying the application Use the Update requires Replacement property on the DB instance in AWS CloudFormation to deploy the application and apply the changes.
- E. Ensure that the DB cluster is a Multi-AZ deployment
- F. Deploy the application with the update
- G. Fail over to the standby instance if verification fails.

**Answer:** A

#### Explanation:

This solution will meet the requirements because it will create a temporary copy of the production database using a snapshot, run the integration tests on the copy, and delete the copy after the tests are done. This way, the production database will not be affected by the code revisions, and the DevOps team can test the changes before deploying them to production. A buildspec file is a YAML file that contains the commands and settings that CodeBuild uses to run a build. The buildspec file can specify the steps to restore the DB cluster from a snapshot, run the integration tests, and drop the restored database.

#### NEW QUESTION 45

A company's development team uses AWS CloudFormation to deploy its application resources. The team must use an interface to make changes to the environment. The team cannot use the AWS Management Console or the AWS CLI to make manual changes directly.

The team uses a developer IAM role to access the environment. The role is configured with the AdministratorAccess managed policy. The company has created a new CloudFormationDeployment IAM role that has the following policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "elasticloadbalancing:*",
        "lambda:*",
        "dynamodb:*"
      ],
      "Resource": "*"
    }
  ]
}
```

The company wants ensure that only CloudFormation can use the new role. The development team cannot make any manual changes to the deployed resources. Which combination of steps meet these requirements? (Select THREE.)

- A. Remove the AdministratorAccess polic
- B. Assign the ReadOnlyAccess managed IAM policy to the developer rol
- C. Instruct the developers to use the CloudFormationDeployment role as a CloudFormation service role when the developers deploy new stacks.
- D. Update the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDepeyment role.
- E. Configure the IAM to be to get and pass the CloudFormationDeployment role if cloudformation actions for resources,
- F. Update the trust Of the CloudFormationDepeyment role to anow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeR01e action
- G. Remove me Administratoraccess polic
- H. Assign the ReadOnly/Access managed IAM policy to the developer role Instruct the developers to assume the CloudFormatondeployment role when the developers new stacks
- I. Add an IAM policy to CloudFormationDeplment to allow cloudformation \* on an Add a policy that allows the iam.PassR01e action for ARN of if iam PassedT0Service equal cloudformation.amazonaws.com

**Answer:** ADF

**Explanation:**

A comprehensive and detailed explanation is:

? Option A is correct because removing the AdministratorAccess policy and assigning the ReadOnlyAccess managed IAM policy to the developer role is a valid way to prevent the developers from making any manual changes to the deployed resources. The AdministratorAccess policy grants full access to all AWS resources and actions, which is not necessary for the developers. The ReadOnlyAccess policy grants read-only access to most AWS resources and actions, which is sufficient for the developers to view the status of their stacks. Instructing the developers to use the CloudFormationDeployment role as a CloudFormation service role when they deploy new stacks is also a valid way to ensure that only CloudFormation can use the new role. A CloudFormation service role is an IAM role that allows CloudFormation to make calls to resources in a stack on behalf of the user1. The user can specify a service role when they create or update a stack, and CloudFormation will use that role's credentials for all operations that are performed on that stack1.

? Option B is incorrect because updating the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDeployment role is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The trust of CloudFormationDeployment role should only allow the cloudformation.amazonaws.com AWS principal to assume the role, as in option D.

? Option C is incorrect because configuring the IAM user to be able to get and pass the CloudFormationDeployment role if cloudformation actions for resources is not a valid solution. This would allow the developers to manually pass the CloudFormationDeployment role to other services or resources, which is not what the company wants. The IAM user should only be able to pass the CloudFormationDeployment role as a service role when they create or update a stack with CloudFormation, as in option A.

? Option D is correct because updating the trust of CloudFormationDeployment role to allow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeRole action is a valid solution. This allows CloudFormation to assume the CloudFormationDeployment role and access resources in other services on behalf of the user2. The trust policy of an IAM role defines which entities can assume the role2. By specifying cloudformation.amazonaws.com as the principal, you grant permission only to CloudFormation to assume this role.

? Option E is incorrect because instructing the developers to assume the CloudFormationDeployment role when they deploy new stacks is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The developers should only use the CloudFormationDeployment role as a service role when they deploy new stacks with CloudFormation, as in option A.

? Option F is correct because adding an IAM policy to CloudFormationDeployment that allows cloudformation:\* on all resources and adding a policy that allows the iam:PassRole action for ARN of CloudFormationDeployment if iam:PassedToService equals cloudformation.amazonaws.com are valid solutions. The first policy grants permission for CloudFormationDeployment to perform any action with any resource using cloudformation.amazonaws.com as a service principal3. The second policy grants permission for passing this role only if it is passed by cloudformation.amazonaws.com as a service principal4. This ensures that only CloudFormation can use this role.

References:

- ? 1: AWS CloudFormation service roles
- ? 2: How to use trust policies with IAM roles
- ? 3: AWS::IAM::Policy
- ? 4: IAM: Pass an IAM role to a specific AWS service

**NEW QUESTION 47**

A company needs to implement failover for its application. The application includes an Amazon CloudFront distribution and a public Application Load Balancer (ALB) in an AWS Region. The company has configured the ALB as the default origin for the distribution.

After some recent application outages, the company wants a zero-second RTO. The company deploys the application to a secondary Region in a warm standby configuration. A DevOps engineer needs to automate the failover of the application to the secondary Region so that HTTP GET requests meet the desired R TO.

Which solution will meet these requirements?

- A. Create a second CloudFront distribution that has the secondary ALB as the default origin
- B. Create Amazon Route 53 alias records that have a failover policy and Evaluate Target Health set to Yes for both CloudFront distribution
- C. Update the application to use the new record set.
- D. Create a new origin on the distribution for the secondary AL
- E. Create a new origin group
- F. Set the original ALB as the primary origin
- G. Configure the origin group to fail over for HTTP 5xx status code
- H. Update the default behavior to use the origin group.
- I. Create Amazon Route 53 alias records that have a failover policy and Evaluate Target Health set to Yes for both ALB
- J. Set the TTL of both records to
- K. Update the distribution's origin to use the new record set.
- L. Create a CloudFront function that detects HTTP 5xx status code
- M. Configure the function to return a 307 Temporary Redirect error response to the secondary ALB if the function detects 5xx status code
- N. Update the distribution's default behavior to send origin responses to the function.

**Answer: B**

**Explanation:**

To implement failover for the application to the secondary Region so that HTTP GET requests meet the desired RTO, the DevOps engineer should use the following solution:

? Create a new origin on the distribution for the secondary ALB. A CloudFront origin is the source of the content that CloudFront delivers to viewers. By creating a new origin for the secondary ALB, the DevOps engineer can configure CloudFront to route traffic to the secondary Region when the primary Region is unavailable<sup>1</sup>

? Create a new origin group. Set the original ALB as the primary origin. Configure the origin group to fail over for HTTP 5xx status codes. An origin group is a logical grouping of two origins: a primary origin and a secondary origin. By creating an origin group, the DevOps engineer can specify which origin CloudFront should use as a fallback when the primary origin fails. The DevOps engineer can also define which HTTP status codes should trigger a failover from the primary origin to the secondary origin. By setting the original ALB as the primary origin and configuring the origin group to fail over for HTTP 5xx status codes, the DevOps engineer can ensure that CloudFront will switch to the secondary ALB when the primary ALB returns server errors<sup>2</sup>

? Update the default behavior to use the origin group. A behavior is a set of rules that CloudFront applies when it receives requests for specific URLs or file types. The default behavior applies to all requests that do not match any other behaviors. By updating the default behavior to use the origin group, the DevOps engineer can enable failover routing for all requests that are sent to the distribution<sup>3</sup>

This solution will meet the requirements because it will automate the failover of the application to the secondary Region with zero-second RTO. When CloudFront receives an HTTP GET request, it will first try to route it to the primary ALB in the primary Region. If the primary ALB is healthy and returns a successful response, CloudFront will deliver it to the viewer. If the primary ALB is unhealthy or returns an HTTP 5xx status code, CloudFront will automatically route the request to the secondary ALB in the secondary Region and deliver its response to the viewer. The other options are not correct because they either do not provide zero-second RTO or do not work as expected. Creating a second CloudFront distribution that has the secondary ALB as the default origin and creating Amazon Route 53 alias records that have a failover policy is not a good option because it will introduce additional latency and complexity to the solution. Route 53 health checks and DNS propagation can take several minutes or longer, which means that viewers might experience delays or errors when accessing the application during a failover event. Creating Amazon Route 53 alias records that have a failover policy and Evaluate Target Health set to Yes for both ALBs and setting the TTL of both records to 0 is not a valid option because it will not work with CloudFront distributions. Route 53 does not support health checks for alias records that point to CloudFront distributions, so it cannot detect if an ALB behind a distribution is healthy or not. Creating a CloudFront function that detects HTTP 5xx status codes and returns a 307 Temporary Redirect error response to the secondary ALB is not a valid option because it will not provide zero-second RTO. A 307 Temporary Redirect error response tells viewers to retry their requests with a different URL, which means that viewers will have to make an additional request and wait for another response from CloudFront before reaching the secondary ALB.

References:

- ? 1: Adding, Editing, and Deleting Origins - Amazon CloudFront
- ? 2: Configuring Origin Failover - Amazon CloudFront
- ? 3: Creating or Updating a Cache Behavior - Amazon CloudFront

**NEW QUESTION 50**

A DevOps engineer needs to configure a blue green deployment for an existing three-tier application. The application runs on Amazon EC2 instances and uses an Amazon RDS database. The EC2 instances run behind an Application Load Balancer (ALB) and are in an Auto Scaling group.

The DevOps engineer has created a launch template and an Auto Scaling group for the blue environment. The DevOps engineer also has created a launch template and an Auto Scaling group for the green environment. Each Auto Scaling group deploys to a matching blue or green target group. The target group also specifies which software blue or green gets loaded on the EC2 instances. The ALB can be configured to send traffic to the blue environment's target group or the green environment's target group. An Amazon Route 53 record for www.example.com points to the ALB.

The deployment must move traffic all at once between the software on the blue environment's EC2 instances to the newly deployed software on the green environment's EC2 instances.

What should the DevOps engineer do to meet these requirements?

- A. Start a rolling restart to the Auto Scaling group for the green environment to deploy the new software on the green environment's EC2 instances. When the rolling restart is complete, use an AWS CLI command to update the ALB to send traffic to the green environment's target group.
- B. Use an AWS CLI command to update the ALB to send traffic to the green environment's target group.
- C. Then start a rolling restart of the Auto Scaling group for the green environment to deploy the new software on the green environment's EC2 instances.
- D. Update the launch template to deploy the green environment's software on the blue environment's EC2 instances. Keep the target groups and Auto Scaling groups unchanged in both environments. Perform a rolling restart of the blue environment's EC2 instances.
- E. Start a rolling restart of the Auto Scaling group for the green environment to deploy the new software on the green environment's EC2 instances. When the rolling restart is complete, update the Route 53 DNS to point to the green environment's endpoint on the ALB.

**Answer: A**

**Explanation:**

This solution will meet the requirements because it will use a rolling restart to gradually replace the EC2 instances in the green environment with new instances that have the new software version installed. A rolling restart is a process that terminates and launches instances in batches, ensuring that there is always a minimum number of healthy instances in service. This way, the green environment can be updated without affecting the availability or performance of the application. When the rolling restart is complete, the DevOps engineer can use an AWS CLI command to modify the listener rules of the ALB and change the default action to forward traffic to the green environment's target group. This will switch the traffic from the blue environment to the green environment all at once, as required by the question.

### NEW QUESTION 53

A security review has identified that an AWS CodeBuild project is downloading a database population script from an Amazon S3 bucket using an unauthenticated request. The security team does not allow unauthenticated requests to S3 buckets for this project. How can this issue be corrected in the MOST secure manner?

- A. Add the bucket name to the AllowedBuckets section of the CodeBuild project setting
- B. Update the build spec to use the AWS CLI to download the database population script.
- C. Modify the S3 bucket settings to enable HTTPS basic authentication and specify a token
- D. Update the build spec to use cURL to pass the token and download the database population script.
- E. Remove unauthenticated access from the S3 bucket with a bucket policy
- F. Modify the service role for the CodeBuild project to include Amazon S3 access
- G. Use the AWS CLI to download the database population script.
- H. Remove unauthenticated access from the S3 bucket with a bucket policy
- I. Use the AWS CLI to download the database population script using an IAM access key and a secret access key.

**Answer: C**

#### Explanation:

A bucket policy is a resource-based policy that defines who can access a specific S3 bucket and what actions they can perform on it. By removing unauthenticated access from the bucket policy, you can prevent anyone without valid credentials from accessing the bucket. A service role is an IAM role that allows an AWS service, such as CodeBuild, to perform actions on your behalf. By modifying the service role for the CodeBuild project to include Amazon S3 access, you can grant the project permission to read and write objects in the S3 bucket. The AWS CLI is a command-line tool that allows you to interact with AWS services, such as S3, using commands in your terminal. By using the AWS CLI to download the database population script, you can leverage the service role credentials and encryption to secure the data transfer.

For more information, you can refer to these web pages:

? [Using bucket policies and user policies - Amazon Simple Storage Service]

? [Create a service role for CodeBuild - AWS CodeBuild]

? [AWS Command Line Interface]

### NEW QUESTION 55

A DevOps engineer is working on a project that is hosted on Amazon Linux and has failed a security review. The DevOps manager has been asked to review the company buildspec.yaml file for an AWS CodeBuild project and provide recommendations. The buildspec.yaml file is configured as follows:

```
env:
  variables:
    AWS_ACCESS_KEY_ID: AKIAJF7BRFWJBA4GHXNA
    AWS_SECRET_ACCESS_KEY: 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
    AWS_DEFAULT_REGION: us-east-1
    DB_PASSWORD: cuj5RptFa3va
  phases:
    build:
      commands:
        - aws s3 cp s3://db-deploy-bucket/my.cnf.template /tmp/my.cnf
        - sed -i '' s/DB_PW/${DB_PASSWORD}/ /tmp/my.cnf
        - aws s3 cp s3://db-deploy-bucket/instance.key /tmp/instance.key
        - chmod 600 /tmp/instance.key
        - scp -i /tmp/instance.key /tmp/my.cnf root@10.25.15.23:/etc/my.cnf
        - ssh -i /tmp/instance.key root@10.25.15.23 /etc/init.d/mysqld restart
```

What changes should be recommended to comply with AWS security best practices? (Select THREE.)

- A. Add a post-build command to remove the temporary files from the container before termination to ensure they cannot be seen by other CodeBuild users.
- B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable.
- C. Store the db\_password as a SecureString value in AWS Systems Manager Parameter Store and then remove the db\_password from the environment variables.
- D. Move the environment variables to the 'db.-deploy-bucket' Amazon S3 bucket, add a prebuild stage to download then export the variables.
- E. Use AWS Systems Manager run command versus scp and ssh commands directly to the instance.

**Answer: BCE**

#### Explanation:

B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable. C. Store the DB\_PASSWORD as a SecureString value in AWS Systems Manager Parameter Store and then remove the DB\_PASSWORD from the environment variables. E. Use AWS Systems Manager run command versus scp and ssh commands directly to the instance.

### NEW QUESTION 58

A company deploys updates to its Amazon API Gateway API several times a week by using an AWS CodePipeline pipeline. As part of the update process the company exports the JavaScript SDK for the API from the API Gateway console and uploads the SDK to an Amazon S3 bucket. The company has configured an Amazon CloudFront distribution that uses the S3 bucket as an origin. Web client then download the SDK by using the CloudFront distribution's endpoint. A DevOps engineer needs to implement a solution to make the new SDK available automatically during new API deployments. Which solution will meet these requirements?

- A. Create a CodePipeline action immediately after the deployment stage of the API
- B. Configure the action to invoke an AWS Lambda function
- C. Configure the Lambda function to download the SDK from API Gateway, upload the SDK to the S3 bucket and create a CloudFront invalidation for the SDK path.
- D. Create a CodePipeline action immediately after the deployment stage of the API. Configure the action to use the CodePipeline integration with API Gateway to export the SDK to Amazon S3. Create another action that uses the CodePipeline integration with Amazon S3 to invalidate the cache for the SDK path.
- E. Create an Amazon EventBridge rule that reacts to UpdateStage events from aws apigateway. Configure the rule to invoke an AWS Lambda function to download the SDK from API Gateway, upload the SDK to the S3 bucket and call the CloudFront API to create an invalidation for the SDK path.

- G. Create an Amazon EventBridge rule that reacts to Create
- H. Deployment events from aws apigatewa
- I. Configure the rule to invoke an AWS Lambda function to download the SDK from AP
- J. Gateway upload the SDK to the S3 bucket and call the S3 API to invalidate the cache for the SDK path.

**Answer:** A

**Explanation:**

This solution would allow the company to automate the process of updating the SDK and making it available to web clients. By adding a CodePipeline action immediately after the deployment stage of the API, the Lambda function will be invoked automatically each time the API is updated. The Lambda function should be able to download the new SDK from API Gateway, upload it to the S3 bucket and also create a CloudFront invalidation for the SDK path so that the latest version of the SDK is available for the web clients. This is the most straight forward solution and it will meet the requirements.

**NEW QUESTION 63**

A company that runs many workloads on AWS has an Amazon EBS spend that has increased over time. The DevOps team notices there are many unattached EBS volumes. Although there are workloads where volumes are detached, volumes over 14 days old are stale and no longer needed. A DevOps engineer has been tasked with creating automation that deletes unattached EBS volumes that have been unattached for 14 days. Which solution will accomplish this?

- A. Configure the AWS Config ec2-volume-inuse-check managed rule with a configuration changes trigger type and an Amazon EC2 volume resource target
- B. Create a new Amazon CloudWatch Events rule scheduled to execute an AWS Lambda function in 14 days to delete the specified EBS volume.
- C. Use Amazon EC2 and Amazon Data Lifecycle Manager to configure a volume lifecycle policy
- D. Set the interval period for unattached EBS volumes to 14 days and set the retention rule to delete
- E. Set the policy target volumes as \*
- F. Create an Amazon CloudWatch Events rule to execute an AWS Lambda function daily
- G. The Lambda function should find unattached EBS volumes and tag them with the current date, and delete unattached volumes that have tags with dates that are more than 14 days old.
- H. Use AWS Trusted Advisor to detect EBS volumes that have been detached for more than 14 days
- I. Execute an AWS Lambda function that creates a snapshot and then deletes the EBS volume.

**Answer:** C

**Explanation:**

The requirement is to create automation that deletes unattached EBS volumes that have been unattached for 14 days. To do this, the DevOps engineer needs to use the following steps:

? Create an Amazon CloudWatch Events rule to execute an AWS Lambda function

daily. CloudWatch Events is a service that enables event-driven architectures by delivering events from various sources to targets. Lambda is a service that lets you

run code without provisioning or managing servers. By creating a CloudWatch Events rule that executes a Lambda function daily, the DevOps engineer can schedule a recurring task to check and delete unattached EBS volumes.

? The Lambda function should find unattached EBS volumes and tag them with the

current date, and delete unattached volumes that have tags with dates that are more than 14 days old. The Lambda function can use the EC2 API to list and filter unattached EBS volumes based on their state and tags. The function can then tag each unattached volume with the current date using the create-tags command. The function can also compare the tag value with the current date and delete any unattached volume that has been tagged more than 14 days ago using the delete-volume command.

**NEW QUESTION 67**

A company has a guideline that every Amazon EC2 instance must be launched from an AMI that the company's security team produces. Every month the security team sends an email message with the latest approved AMIs to all the development teams.

The development teams use AWS CloudFormation to deploy their applications. When developers launch a new service they have to search their email for the latest AMIs that the security department sent. A DevOps engineer wants to automate the process that the security team uses to provide the AMI IDs to the development teams.

What is the MOST scalable solution that meets these requirements?

- A. Direct the security team to use CloudFormation to create new versions of the AMIs and to list the AMI ARNs in an encrypted Amazon S3 object as part of the stack's Outputs Section. Instruct the developers to use a cross-stack reference to load the encrypted S3 object and obtain the most recent AMI ARNs.
- B. Direct the security team to use a CloudFormation stack to create an AWS CodePipeline pipeline that builds new AMIs and places the latest AMI ARNs in an encrypted Amazon S3 object as part of the pipeline output. Instruct the developers to use a cross-stack reference within their own CloudFormation template to obtain the S3 object location and the most recent AMI ARNs.
- C. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to place the AMI ARNs as parameters in AWS Systems Manager Parameter Store. Instruct the developers to specify a parameter of type SSM in their CloudFormation stack to obtain the most recent AMI ARNs from Parameter Store.
- D. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to create an Amazon Simple Notification Service (Amazon SNS) topic so that every development team can receive notification.
- E. When the development teams receive a notification, instruct them to write an AWS Lambda function that will update their CloudFormation stack with the most recent AMI ARNs.

**Answer:** C

**Explanation:**

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/dynamic-references.html>

**NEW QUESTION 68**

A DevOps engineer is building a continuous deployment pipeline for a serverless application that uses AWS Lambda functions. The company wants to reduce the customer impact of an unsuccessful deployment. The company also wants to monitor for issues.

Which deployment stage configuration will meet these requirements?

- A. Use an AWS Serverless Application Model (AWS SAM) template to define the serverless application
- B. Use AWS CodeDeploy to deploy the Lambda functions with the Canary10Percent15Minutes Deployment Preference Type
- C. Use Amazon CloudWatch alarms to monitor the health of the functions.

- D. Use AWS CloudFormation to publish a new stack update, and include Amazon CloudWatch alarms on all resource
- E. Set up an AWS CodePipeline approval action for a developer to verify and approve the AWS CloudFormation change set.
- F. Use AWS CloudFormation to publish a new version on every stack update, and include Amazon CloudWatch alarms on all resource
- G. Use the RoutingConfig property of the AWS::Lambda::Alias resource to update the traffic routing during the stack update.
- H. Use AWS CodeBuild to add sample event payloads for testing to the Lambda function
- I. Publish a new version of the functions, and include Amazon CloudWatch alarm
- J. Update the production alias to point to the new versio
- K. Configure rollbacks to occur when an alarm is in the ALARM state.

**Answer: D**

**Explanation:**

Use routing configuration on an alias to send a portion of traffic to a second function version. For example, you can reduce the risk of deploying a new version by configuring the alias to send most of the traffic to the existing version, and only a small percentage of traffic to the new version.

<https://docs.aws.amazon.com/lambda/latest/dg/configuration-aliases.html>

The following are the steps involved in the deploy stage configuration that will meet the requirements:

? Use AWS CodeBuild to add sample event payloads for testing to the Lambda functions.

? Publish a new version of the functions, and include Amazon CloudWatch alarms.

? Update the production alias to point to the new version.

? Configure rollbacks to occur when an alarm is in the ALARM state.

This configuration will help to reduce the customer impact of an unsuccessful deployment

by deploying the new version of the functions to a staging environment first. This will allow the DevOps engineer to test the new version of the functions before deploying it to production.

The configuration will also help to monitor for issues by including Amazon CloudWatch alarms. These alarms will alert the DevOps engineer if there are any problems with the new version of the functions.

**NEW QUESTION 71**

A rapidly growing company wants to scale for developer demand for AWS development environments. Development environments are created manually in the AWS Management Console. The networking team uses AWS CloudFormation to manage the networking infrastructure, exporting stack output values for the Amazon VPC and all subnets. The development environments have common standards, such as Application Load Balancers, Amazon EC2 Auto Scaling groups, security groups, and Amazon DynamoDB tables.

To keep up with demand, the DevOps engineer wants to automate the creation of development environments. Because the infrastructure required to support the application is expected to grow, there must be a way to easily update the deployed infrastructure. CloudFormation will be used to create a template for the development environments.

Which approach will meet these requirements and quickly provide consistent AWS environments for developers?

- A. Use Fn::ImportValue intrinsic functions in the Resources section of the template to retrieve Virtual Private Cloud (VPC) and subnet value
- B. Use CloudFormation StackSets for the development environments, using the Count input parameter to indicate the number of environments needed
- C. Use the UpdateStackSet command to update existing development environments.
- D. Use nested stacks to define common infrastructure component
- E. To access the exported values, use TemplateURL to reference the networking team's template
- F. To retrieve Virtual Private Cloud (VPC) and subnet values, use Fn::ImportValue intrinsic functions in the Parameters section of the root template
- G. Use the CreateChangeSet and ExecuteChangeSet commands to update existing development environments.
- H. Use nested stacks to define common infrastructure component
- I. Use Fn::ImportValue intrinsic functions with the resources of the nested stack to retrieve Virtual Private Cloud (VPC) and subnet value
- J. Use the CreateChangeSet and ExecuteChangeSet commands to update existing development environments.
- K. Use Fn::ImportValue intrinsic functions in the Parameters section of the root template to retrieve Virtual Private Cloud (VPC) and subnet value
- L. Define the development resources in the order they need to be created in the CloudFormation nested stack
- M. Use the CreateChangeSet
- N. and ExecuteChangeSet commands to update existing development environments.

**Answer: C**

**Explanation:**

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference-importvalue.html>

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference-importvalue.html> CF of network exports the VPC, subnet or needed information CF of application imports the above information to its stack and UpdateChangeSet/ ExecuteChangeSet

**NEW QUESTION 75**

A company uses an organization in AWS Organizations that has all features enabled. The company uses AWS Backup in a primary account and uses an AWS Key Management Service (AWS KMS) key to encrypt the backups.

The company needs to automate a cross-account backup of the resources that AWS Backup backs up in the primary account. The company configures cross-account backup in the Organizations management account. The company creates a new AWS account in the organization and configures an AWS Backup backup vault in the new account. The company creates a KMS key in the new account to encrypt the backups. Finally, the company configures a new backup plan in the primary account. The destination for the new backup plan is the backup vault in the new account.

When the AWS Backup job in the primary account is invoked, the job creates backups in the primary account. However, the backups are not copied to the new account's backup vault.

Which combination of steps must the company take so that backups can be copied to the new account's backup vault? (Select TWO.)

- A. Edit the backup vault access policy in the new account to allow access to the primary account.
- B. Edit the backup vault access policy in the primary account to allow access to the new account.
- C. Edit the backup vault access policy in the primary account to allow access to the KMS key in the new account.
- D. Edit the key policy of the KMS key in the primary account to share the key with the new account.
- E. Edit the key policy of the KMS key in the new account to share the key with the primary account.

**Answer: AE**

**Explanation:**

To enable cross-account backup, the company needs to grant permissions to both the backup vault and the KMS key in the destination account. The backup vault access policy in the destination account must allow the primary account to copy backups into the vault. The key policy of the KMS key in the destination account

must allow the primary account to use the key to encrypt and decrypt the backups. These steps are described in the AWS documentation<sup>12</sup>. Therefore, the correct answer is A and E.

References:

? 1: Creating backup copies across AWS accounts - AWS Backup

? 2: Using AWS Backup with AWS Organizations - AWS Backup

**NEW QUESTION 77**

A company manages multiple AWS accounts in AWS Organizations. The company's security policy states that AWS account root user credentials for member accounts must not be used. The company monitors access to the root user credentials.

A recent alert shows that the root user in a member account launched an Amazon EC2 instance. A DevOps engineer must create an SCP at the organization's root level that will prevent the root user in member accounts from making any AWS service API calls.

Which SCP will meet these requirements?

A)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

B)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Principal": { "AWS": "arn:aws:iam::*:root" }
    }
  ]
}
```

C)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

D)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Principal": "root"
    }
  ]
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: D**

#### NEW QUESTION 80

A DevOps engineer has implemented a CI/CO pipeline to deploy an AWS Cloud Formation template that provisions a web application. The web application consists of an Application Load Balancer (ALB) a target group, a launch template that uses an Amazon Linux 2 AMI an Auto Scaling group of Amazon EC2 instances, a security group and an Amazon RDS for MySQL database The launch template includes user data that specifies a script to install and start the application.

The initial deployment of the application was successful. The DevOps engineer made changes to update the version of the application with the user data. The CI/CD pipeline has deployed a new version of the template However, the health checks on the ALB are now failing The health checks have marked all targets as unhealthy.

During investigation the DevOps engineer notices that the Cloud Formation stack has a status of UPDATE\_COMPLETE. However, when the DevOps engineer connects to one of the EC2 instances and checks /varar/log messages, the DevOps engineer notices that the Apache web server failed to start successfully because of a configuration error

How can the DevOps engineer ensure that the CloudFormation deployment will fail if the user data fails to successfully finish running?

- A. Use the cfn-signal helper script to signal success or failure to CloudFormation Use the WaitOnResourceSignals update policy within the CloudFormation template Set an appropriate timeout for the update policy.
- B. Create an Amazon CloudWatch alarm for the UnhealthyHostCount metri
- C. Include an appropriate alarm threshold for the target group Create an Amazon Simple Notification Service (Amazon SNS) topic as the target to signal success or failure to CloudFormation
- D. Create a lifecycle hook on the Auto Scaling group by using the AWS AutoScaling LifecycleHook resource Create an Amazon Simple Notification Service (Amazon SNS) topic as the target to signal success or failure to CloudFormation Set an appropriate timeout on the lifecycle hook.
- E. Use the Amazon CloudWatch agent to stream the cloud-init logs Create a subscription filter that includes an AWS Lambda function with an appropriate invocation timeout Configure the Lambda function to use the SignalResource API operation to signal success or failure to CloudFormation.

**Answer: A**

#### Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-attribute-updatepolicy.html>

#### NEW QUESTION 85

An ecommerce company has chosen AWS to host its new platform. The company's DevOps team has started building an AWS Control Tower landing zone. The DevOps team has set the identity store within AWS IAM Identity Center (AWS Single Sign-On) to external identity provider (IdP) and has configured SAML 2.0. The DevOps team wants a robust permission model that applies the principle of least privilege. The model must allow the team to build and manage only the team's own resources.

Which combination of steps will meet these requirements? (Choose three.)

- A. Create IAM policies that include the required permission
- B. Include the aws:PrincipalTag condition key.
- C. Create permission set
- D. Attach an inline policy that includes the required permissions and uses the aws:PrincipalTag condition key to scope the permissions.
- E. Create a group in the Id
- F. Place users in the grou
- G. Assign the group to accounts and the permission sets in IAM Identity Center.
- H. Create a group in the Id
- I. Place users in the grou
- J. Assign the group to OUs and IAM policies.
- K. Enable attributes for access control in IAM Identity Cente
- L. Apply tags to user
- M. Map the tags as key-value pairs.
- N. Enable attributes for access control in IAM Identity Cente
- O. Map attributes from the IdP as key-value pairs.

**Answer: BCF**

**Explanation:**

Using the principalTag in the Permission Set inline policy a logged in user belonging to a specific AD group in the IDP can be permitted access to perform operations on certain resources if their group matches the group used in the PrincipleTag. Basically you are narrowing the scope of privileges assigned via Permission policies conditionally based on whether the logged in user belongs to a specific AD Group in IDP. The mapping of the AD group to the request attributes can be done using SSO attributes where we can pass other attributes like the SAML token as well.  
<https://docs.aws.amazon.com/singlesignon/latest/userguide/abac.html>

**NEW QUESTION 87**

A development team wants to use AWS CloudFormation stacks to deploy an application. However, the developer IAM role does not have the required permissions to provision the resources that are specified in the AWS CloudFormation template. A DevOps engineer needs to implement a solution that allows the developers to deploy the stacks. The solution must follow the principle of least privilege. Which solution will meet these requirements?

- A. Create an IAM policy that allows the developers to provision the required resource
- B. Attach the policy to the developer IAM role.
- C. Create an IAM policy that allows full access to AWS CloudFormation
- D. Attach the policy to the developer IAM role.
- E. Create an AWS CloudFormation service role that has the required permission
- F. Grant the developer IAM role a cloudformation:\* action
- G. Use the new service role during stack deployments.
- H. Create an AWS CloudFormation service role that has the required permission
- I. Grant the developer IAM role the iam:PassRole permission
- J. Use the new service role during stack deployments.

**Answer: D**

**Explanation:**

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-iam-service-role.html>

**NEW QUESTION 90**

AnyCompany is using AWS Organizations to create and manage multiple AWS accounts. AnyCompany recently acquired a smaller company, Example Corp. During the acquisition process, Example Corp's single AWS account joined AnyCompany's management account through an Organizations invitation. AnyCompany moved the new member account under an OU that is dedicated to Example Corp. AnyCompany's DevOps engineer has an IAM user that assumes a role that is named OrganizationAccountAccessRole to access member accounts. This role is configured with a full access policy. When the DevOps engineer tries to use the AWS Management Console to assume the role in Example Corp's new member account, the DevOps engineer receives the following error message: "Invalid information in one or more fields. Check your information or contact your administrator." Which solution will give the DevOps engineer access to the new member account?

- A. In the management account, grant the DevOps engineer's IAM user permission to assume the OrganizationAccountAccessRole IAM role in the new member account.
- B. In the management account, create a new SCP. In the SCP, grant the DevOps engineer's IAM user full access to all resources in the new member account.
- C. Attach the SCP to the OU that contains the new member account.
- D. In the new member account, create a new IAM role that is named OrganizationAccountAccessRole.
- E. Attach the AdministratorAccess AWS managed policy to the role.
- F. In the role's trust policy, grant the management account permission to assume the role.
- G. In the new member account, edit the trust policy for the OrganizationAccountAccessRole IAM role.
- H. Grant the management account permission to assume the role.

**Answer: C**

**Explanation:**

The problem is that the DevOps engineer cannot assume the OrganizationAccountAccessRole IAM role in the new member account that joined AnyCompany's management account through an Organizations invitation. The solution is to create a new IAM role with the same name and trust policy in the new member account.

? Option A is incorrect, as it does not address the root cause of the error. The DevOps engineer's IAM user already has permission to assume the OrganizationAccountAccessRole IAM role in any member account, as this is the default role name that AWS Organizations creates when a new account joins an organization. The error occurs because the new member account does not have this role, as it was not created by AWS Organizations.

? Option B is incorrect, as it does not address the root cause of the error. An SCP is a policy that defines the maximum permissions for account members of an organization or organizational unit (OU). An SCP does not grant permissions to IAM users or roles, but rather limits the permissions that identity-based policies or resource-based policies grant to them. An SCP also does not affect how IAM roles are assumed by other principals.

? Option C is correct, as it addresses the root cause of the error. By creating a new IAM role with the same name and trust policy as the OrganizationAccountAccessRole IAM role in the new member account, the DevOps engineer can assume this role and access the account. The new role should have the AdministratorAccess AWS managed policy attached, which grants full access to all AWS resources in the account. The trust policy should allow the management account to assume the role, which can be done by specifying the management account ID as a principal in the policy statement.

? Option D is incorrect, as it assumes that the new member account already has the OrganizationAccountAccessRole IAM role, which is not true. The new member account does not have this role, as it was not created by AWS Organizations. Editing the trust policy of a non-existent role will not solve the problem.

**NEW QUESTION 91**

A company uses AWS Secrets Manager to store a set of sensitive API keys that an AWS Lambda function uses. When the Lambda function is invoked, the Lambda function retrieves the API keys and makes an API call to an external service. The Secrets Manager secret is encrypted with the default AWS Key Management Service (AWS KMS) key.

A DevOps engineer needs to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Update the default KMS key for Secrets Manager to allow only the Lambda function's execution role to decrypt.
- B. Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt.
- C. Update Secrets Manager to use the new customer managed key.
- D. Create a KMS customer managed key that trusts Secrets Manager and allows the account's :root principal to decrypt.

- E. Update Secrets Manager to use the new customer managed key.
- F. Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level.
- G. Configure the permissions so that the KMS key can encrypt the Secrets Manager secret.
- H. Remove all KMS permissions from the Lambda function's execution role.

**Answer:** BD

**Explanation:**

The requirement is to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege, which means granting the minimum permissions necessary to perform a task.

To do this, the DevOps engineer needs to use the following steps:

? Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt. A customer managed key is a symmetric encryption key that is fully managed by the customer. The customer can define the key policy, which specifies who can use and manage the key. By creating a customer managed key, the DevOps engineer can restrict the decryption permission to only the Lambda function's execution role, and prevent other principals from accessing the secret values. The customer managed key also needs to trust Secrets Manager, which means allowing Secrets Manager to use the key to encrypt and decrypt secrets on behalf of the customer.

? Update Secrets Manager to use the new customer managed key. Secrets Manager allows customers to choose which KMS key to use for encrypting each secret. By default, Secrets Manager uses the default KMS key for Secrets Manager, which is a service-managed key that is shared by all customers in the same AWS Region. By updating Secrets Manager to use the new customer managed key, the DevOps engineer can ensure that only the Lambda function's execution role can decrypt the secret values using that key.

? Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level. The Lambda function's execution role is an IAM role that grants permissions to the Lambda function to access AWS services and resources. The role needs to have KMS permissions to use the customer managed key for decryption. However, to apply the principle of least privilege, the role should have the permissions scoped on the resource level, which means specifying the ARN of the customer managed key as a condition in the IAM policy statement. This way, the role can only use that specific key and not any other KMS keys in the account.

**NEW QUESTION 96**

A developer is maintaining a fleet of 50 Amazon EC2 Linux servers. The servers are part of an Amazon EC2 Auto Scaling group, and also use Elastic Load Balancing for load balancing.

Occasionally, some application servers are being terminated after failing ELB HTTP health checks. The developer would like to perform a root cause analysis on the issue, but before being able to access application logs, the server is terminated.

How can log collection be automated?

- A. Use Auto Scaling lifecycle hooks to put instances in a Pending:Wait stat
- B. Create an Amazon CloudWatch alarm for EC2 Instance Terminate Successful and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- C. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- D. Create an AWS Config rule for EC2 Instance-terminate Lifecycle Action and trigger a step function that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- E. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- F. Create an Amazon CloudWatch subscription filter for EC2 Instance Terminate Successful and trigger a CloudWatch agent that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- G. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- H. Create an Amazon EventBridge rule for EC2 Instance-terminate Lifecycle Action and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.

**Answer:** D

**Explanation:**

<https://blog.fourninecloud.com/auto-scaling-lifecycle-hooks-to-export-server-logs-when-instance-terminating-58e06d7c0d6a>

**NEW QUESTION 97**

A DevOps engineer manages a web application that runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The instances run in an EC2 Auto Scaling group across multiple Availability Zones. The engineer needs to implement a deployment strategy that:

Launches a second fleet of instances with the same capacity as the original fleet. Maintains the original fleet unchanged while the second fleet is launched.

Transitions traffic to the second fleet when the second fleet is fully deployed. Terminates the original fleet automatically 1 hour after transition.

Which solution will satisfy these requirements?

- A. Use an AWS CloudFormation template with a retention policy for the ALB set to 1 hour
- B. Update the Amazon Route 53 record to reflect the new ALB.
- C. Use two AWS Elastic Beanstalk environments to perform a blue/green deployment from the original environment to the new one
- D. Create an application version lifecycle policy to terminate the original environment in 1 hour.
- E. Use AWS CodeDeploy with a deployment group configured with a blue/green deployment configuration. Select the option Terminate the original instances in the deployment group with a waiting period of 1 hour.
- F. Use AWS Elastic Beanstalk with the configuration set to Immutable
- G. Create an .ebextension using the Resources key that sets the deletion policy of the ALB to 1 hour, and deploy the application.

**Answer:** C

**Explanation:**

[https://docs.aws.amazon.com/codedeploy/latest/APIReference/API\\_BlueInstanceTerminationOption.html](https://docs.aws.amazon.com/codedeploy/latest/APIReference/API_BlueInstanceTerminationOption.html)

The original revision termination settings are configured to wait 1 hour after traffic has been rerouted before terminating the blue task set.

<https://docs.aws.amazon.com/AmazonECS/latest/developerguide/deployment-type-bluegreen.html>

**NEW QUESTION 99**

A company has an application that includes AWS Lambda functions. The Lambda functions run Python code that is stored in an AWS CodeCommit repository. The company has recently experienced failures in the production environment because of an error in the Python code. An engineer has written unit tests for the Lambda functions to help avoid releasing any future defects into the production environment.

The company's DevOps team needs to implement a solution to integrate the unit tests into an existing AWS CodePipeline pipeline. The solution must produce reports about the unit tests for the company to view.

Which solution will meet these requirements?

- A. Associate the CodeCommit repository with Amazon CodeGuru Reviewer
- B. Create a new AWS CodeBuild project
- C. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild project
- D. Create a buildspec.yml file in the CodeCommit repository
- E. In the buildspec.yml file, define the actions to run a CodeGuru review.
- F. Create a new AWS CodeBuild project
- G. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild project
- H. Create a CodeBuild report group
- I. Create a buildspec.yml file in the CodeCommit repository
- J. In the buildspec.yml file, define the actions to run the unit tests with an output of JUNITXML in the build phase section. Configure the test reports to be uploaded to the new CodeBuild report group.
- K. Create a new AWS CodeArtifact repository
- L. Create a new AWS CodeBuild project
- M. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild project
- N. Create an appspec.yml file in the original CodeCommit repository
- O. In the appspec.yml file, define the actions to run the unit tests with an output of CUCUMBERJSON in the build phase section
- P. Configure the test reports to be sent to the new CodeArtifact repository.
- Q. Create a new AWS CodeBuild project
- R. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild project
- S. Create a new Amazon S3 bucket
- T. Create a buildspec.yml file in the CodeCommit repository
- . In the buildspec.yml file, define the actions to run the unit tests with an output of HTML in the build phase section
- . In the reports section, upload the test reports to the S3 bucket.

**Answer: B**

**Explanation:**

The correct answer is B. Creating a new AWS CodeBuild project and configuring a test stage in the AWS CodePipeline pipeline that uses the new CodeBuild project is the best way to integrate the unit tests into the existing pipeline. Creating a CodeBuild report group and uploading the test reports to the new CodeBuild report group will produce reports about the unit tests for the company to view. Using JUNITXML as the output format for the unit tests is supported by CodeBuild and will generate a valid report. Option A is incorrect because Amazon CodeGuru Reviewer is a service that provides automated code reviews and recommendations for improving code quality and performance. It is not a tool for running unit tests or producing test reports. Therefore, option A will not meet the requirements.

Option C is incorrect because AWS CodeArtifact is a service that provides secure, scalable, and cost-effective artifact management for software development. It is not a tool for running unit tests or producing test reports. Moreover, option C uses CUCUMBERJSON as the output format for the unit tests, which is not supported by CodeBuild and will not generate a valid report.

Option D is incorrect because uploading the test reports to an Amazon S3 bucket is not the best way to produce reports about the unit tests for the company to view. CodeBuild has a built-in feature to create and manage test reports, which is more convenient and efficient than using S3. Furthermore, option D uses HTML as the output format for the unit tests, which is not supported by CodeBuild and will not generate a valid report.

**NEW QUESTION 100**

A business has an application that consists of five independent AWS Lambda functions.

The DevOps engineer has built a CI/CD pipeline using AWS CodePipeline and AWS CodeBuild that builds test packages and deploys each Lambda function in sequence. The pipeline uses an Amazon EventBridge rule to ensure the pipeline starts as quickly as possible after a change is made to the application source code.

After working with the pipeline for a few months the DevOps engineer has noticed the pipeline takes too long to complete.

What should the DevOps engineer implement to BEST improve the speed of the pipeline?

- A. Modify the CodeBuild projects within the pipeline to use a compute type with more available network throughput.
- B. Create a custom CodeBuild execution environment that includes a symmetric multiprocessing configuration to run the builds in parallel.
- C. Modify the CodePipeline configuration to run actions for each Lambda function in parallel by specifying the same runOrder.
- D. Modify each CodeBuild project to run within a VPC and use dedicated instances to increase throughput.

**Answer: C**

**Explanation:**

<https://docs.aws.amazon.com/codepipeline/latest/userguide/reference-pipeline-structure.html>

AWS doc: "To specify parallel actions, use the same integer for each action you want to run in parallel. For example, if you want three actions to run in sequence in a stage, you would give the first action the runOrder value of 1, the second action the runOrder value of 2, and the third the runOrder value of 3. However, if you want the second and third actions to run in parallel, you would give the first action the runOrder value of 1 and both the second and third actions the runOrder value of 2."

**NEW QUESTION 103**

A company uses AWS Storage Gateway in file gateway mode in front of an Amazon S3 bucket that is used by multiple resources. In the morning when business begins, users do not see the objects processed by a third party the previous evening. When a DevOps engineer looks directly at the S3 bucket, the data is there, but it is missing in Storage Gateway.

Which solution ensures that all the updated third-party files are available in the morning?

- A. Configure a nightly Amazon EventBridge event to invoke an AWS Lambda function to run the RefreshCache command for Storage Gateway.
- B. Instruct the third party to put data into the S3 bucket using AWS Transfer for SFTP.
- C. Modify Storage Gateway to run in volume gateway mode.
- D. Use S3 Same-Region Replication to replicate any changes made directly in the S3 bucket to Storage Gateway.

**Answer: A**

**Explanation:**

[https://docs.aws.amazon.com/storagegateway/latest/APIReference/API\\_RefreshCache.html](https://docs.aws.amazon.com/storagegateway/latest/APIReference/API_RefreshCache.html) "It only updates the cached inventory to reflect changes in the inventory of the objects in the S3 bucket. This operation is only supported in the S3 File Gateway types."

### NEW QUESTION 108

A company is using AWS to run digital workloads. Each application team in the company has its own AWS account for application hosting. The accounts are consolidated in an organization in AWS Organizations. The company wants to enforce security standards across the entire organization. To avoid noncompliance because of security misconfiguration, the company has enforced the use of AWS CloudFormation. A production support team can modify resources in the production environment by using the AWS Management Console to troubleshoot and resolve application-related issues. A DevOps engineer must implement a solution to identify in near real time any AWS service misconfiguration that results in noncompliance. The solution must automatically remediate the issue within 15 minutes of identification. The solution also must track noncompliant resources and events in a centralized dashboard with accurate timestamps. Which solution will meet these requirements with the LEAST development overhead?

- A. Use CloudFormation drift detection to identify noncompliant resource
- B. Use drift detection events from CloudFormation to invoke an AWS Lambda function for remediation
- C. Configure the Lambda function to publish logs to an Amazon CloudWatch Logs log group
- D. Configure an Amazon CloudWatch dashboard to use the log group for tracking.
- E. Turn on AWS CloudTrail in the AWS account
- F. Analyze CloudTrail logs by using Amazon Athena to identify noncompliant resource
- G. Use AWS Step Functions to track query results on Athena for drift detection and to invoke an AWS Lambda function for remediation
- H. For tracking, set up an Amazon QuickSight dashboard that uses Athena as the data source.
- I. Turn on the configuration recorder in AWS Config in all the AWS accounts to identify noncompliant resource
- J. Enable AWS Security Hub with the `--no-enable-default-standards` option in all the AWS account
- K. Set up AWS Config managed rules and custom rule
- L. Set up automatic remediation by using AWS Config conformance pack
- M. For tracking, set up a dashboard on Security Hub in a designated Security Hub administrator account.
- N. Turn on AWS CloudTrail in the AWS account
- O. Analyze CloudTrail logs by using Amazon CloudWatch Logs to identify noncompliant resource
- P. Use CloudWatch Logs filters for drift detection
- Q. Use Amazon EventBridge to invoke the Lambda function for remediation
- R. Stream filtered CloudWatch logs to Amazon OpenSearch Service
- S. Set up a dashboard on OpenSearch Service for tracking.

**Answer: C**

#### Explanation:

The best solution is to use AWS Config and AWS Security Hub to identify and remediate noncompliant resources across multiple AWS accounts. AWS Config enables continuous monitoring of the configuration of AWS resources and evaluates them against desired configurations. AWS Config can also automatically remediate noncompliant resources by using conformance packs, which are a collection of AWS Config rules and remediation actions that can be deployed as a single entity. AWS Security Hub provides a comprehensive view of the security posture of AWS accounts and resources. AWS Security Hub can aggregate and normalize the findings from AWS Config and other AWS services, as well as from partner solutions. AWS Security Hub can also be used to create a dashboard for tracking noncompliant resources and events in a centralized location.

The other options are not optimal because they either require more development overhead, do not provide near real time detection and remediation, or do not provide a centralized dashboard for tracking.

Option A is not optimal because CloudFormation drift detection is not a near real time solution. Drift detection has to be manually initiated on each stack or resource, or scheduled using a cron expression. Drift detection also does not provide remediation actions, so a custom Lambda function has to be developed and invoked. CloudWatch Logs and dashboard can be used for tracking, but they do not provide a comprehensive view of the security posture of the AWS accounts and resources.

Option B is not optimal because CloudTrail logs analysis using Athena is not a near real time solution. Athena queries have to be manually run or scheduled using a cron expression. Athena also does not provide remediation actions, so a custom Lambda function has to be developed and invoked. Step Functions can be used to orchestrate the query and remediation workflow, but it adds more complexity and cost. QuickSight dashboard can be used for tracking, but it does not provide a comprehensive view of the security posture of the AWS accounts and resources.

Option D is not optimal because CloudTrail logs analysis using CloudWatch Logs is not a near real time solution. CloudWatch Logs filters have to be manually created or updated for each resource type and configuration change. CloudWatch Logs also does not provide remediation actions, so a custom Lambda function has to be developed and invoked. EventBridge can be used to trigger the Lambda function, but it adds more complexity and cost. OpenSearch Service dashboard can be used for tracking, but it does not provide a comprehensive view of the security posture of the AWS accounts and resources. References:

- ? AWS Config conformance packs
- ? Introducing AWS Config conformance packs
- ? Managing conformance packs across all accounts in your organization

### NEW QUESTION 113

A company is using AWS CodePipeline to automate its release pipeline. AWS CodeDeploy is being used in the pipeline to deploy an application to Amazon Elastic Container Service (Amazon ECS) using the blue/green deployment model. The company wants to implement scripts to test the green version of the application before shifting traffic. These scripts will complete in 5 minutes or less. If errors are discovered during these tests, the application must be rolled back. Which strategy will meet these requirements?

- A. Add a stage to the CodePipeline pipeline between the source and deploy stage
- B. Use AWS CodeBuild to create a runtime environment and build commands in the buildspec file to invoke test script
- C. If errors are found, use the `aws deploy stop-deployment` command to stop the deployment.
- D. Add a stage to the CodePipeline pipeline between the source and deploy stage
- E. Use this stage to invoke an AWS Lambda function that will run the test script
- F. If errors are found, use the `aws deploy stop-deployment` command to stop the deployment.
- G. Add a hooks section to the CodeDeploy AppSpec file
- H. Use the `AfterAllowTestTraffic` lifecycle event to invoke an AWS Lambda function to run the test script
- I. If errors are found, exit the Lambda function with an error to initiate rollback.
- J. Add a hooks section to the CodeDeploy AppSpec file
- K. Use the `AfterAllowTraffic` lifecycle event to invoke the test script
- L. If errors are found, use the `aws deploy stop-deployment` CLI command to stop the deployment.

**Answer: C**

#### Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/reference-appspec-file-structure-hooks.html>

#### NEW QUESTION 115

A company's production environment uses an AWS CodeDeploy blue/green deployment to deploy an application. The deployment includes Amazon EC2 Auto Scaling groups that launch instances that run Amazon Linux 2.

A working appspec. yml file exists in the code repository and contains the following text.

```
version: 0.0
os: linux
files:
  - source: /
    destination: /var/www/html/application
```

A DevOps engineer needs to ensure that a script downloads and installs a license file onto the instances before the replacement instances start to handle request traffic. The DevOps engineer adds a hooks section to the appspec. yml file.

Which hook should the DevOps engineer use to run the script that downloads and installs the license file?

- A. AfterBlockTraffic
- B. BeforeBlockTraffic
- C. BeforeInstall
- D. Download Bundle

**Answer: C**

#### Explanation:

This hook runs before the new application version is installed on the replacement instances. This is the best place to run the script because it ensures that the license file is downloaded and installed before the replacement instances start to handle request traffic. If you use any other hook, you may encounter errors or inconsistencies in your application.

#### NEW QUESTION 120

A company has an on-premises application that is written in Go. A DevOps engineer must move the application to AWS. The company's development team wants to enable blue/green deployments and perform A/B testing.

Which solution will meet these requirements?

- A. Deploy the application on an Amazon EC2 instance, and create an AMI of the instance
- B. Use the AMI to create an automatic scaling launch configuration that is used in an Auto Scaling group
- C. Use Elastic Load Balancing to distribute traffic
- D. When changes are made to the application, a new AMI will be created, which will initiate an EC2 instance refresh.
- E. Use Amazon Lightsail to deploy the application
- F. Store the application in a zipped format in an Amazon S3 bucket
- G. Use this zipped version to deploy new versions of the application to Lightsail
- H. Use Lightsail deployment options to manage the deployment.
- I. Use AWS CodeArtifact to store the application code
- J. Use AWS CodeDeploy to deploy the application to a fleet of Amazon EC2 instances
- K. Use Elastic Load Balancing to distribute the traffic to the EC2 instance
- L. When making changes to the application, upload a new version to CodeArtifact and create a new CodeDeploy deployment.
- M. Use AWS Elastic Beanstalk to host the application
- N. Store a zipped version of the application in Amazon S3. Use that location to deploy new versions of the application
- O. Use Elastic Beanstalk to manage the deployment options.

**Answer: D**

#### Explanation:

<https://aws.amazon.com/quickstart/architecture/blue-green-deployment/>

#### NEW QUESTION 122

A company builds a container image in an AWS CodeBuild project by running Docker commands. After the container image is built, the CodeBuild project uploads the container image to an Amazon S3 bucket. The CodeBuild project has an IAM service role that has permissions to access the S3 bucket.

A DevOps engineer needs to replace the S3 bucket with an Amazon Elastic Container Registry (Amazon ECR) repository to store the container images. The DevOps engineer creates an ECR private image repository in the same AWS Region of the CodeBuild project. The DevOps engineer adjusts the IAM service role with the permissions that are necessary to work with the new ECR repository. The DevOps engineer also places new repository information into the docker build command and the docker push command that are used in the buildspec.yml file.

When the CodeBuild project runs a build job, the job fails when the job tries to access the ECR repository.

Which solution will resolve the issue of failed access to the ECR repository?

- A. Update the buildspec.yml file to log in to the ECR repository by using the aws ecr get-login-password AWS CLI command to obtain an authentication token
- B. Update the docker login command to use the authentication token to access the ECR repository.
- C. Add an environment variable of type SECRETS\_MANAGER to the CodeBuild project
- D. In the environment variable, include the ARN of the CodeBuild project's IAM service role
- E. Update the buildspec.yml file to use the new environment variable to log in with the docker login command to access the ECR repository.
- F. Update the ECR repository to be a public image repository
- G. Add an ECR repository policy that allows the IAM service role to have access.
- H. Update the buildspec.yml file to use the AWS CLI to assume the IAM service role for ECR operation
- I. Add an ECR repository policy that allows the IAM service role to have access.

**Answer: A**

#### Explanation:

(A) When Docker communicates with an Amazon Elastic Container Registry (ECR) repository, it requires authentication. You can authenticate your Docker client

to the Amazon ECR registry with the help of the AWS CLI (Command Line Interface). Specifically, you can use the "aws ecr get-login-password" command to get an authorization token and then use Docker's "docker login" command with that token to authenticate to the registry. You would need to perform these steps in your buildspec.yml file before attempting to push or pull images from/to the ECR repository.

#### NEW QUESTION 126

A company uses an organization in AWS Organizations to manage its AWS accounts. The company recently acquired another company that has standalone AWS accounts. The acquiring company's DevOps team needs to consolidate the administration of the AWS accounts for both companies and retain full administrative control of the accounts. The DevOps team also needs to collect and group findings across all the accounts to implement and maintain a security posture. Which combination of steps should the DevOps team take to meet these requirements? (Select TWO.)

- A. Invite the acquired company's AWS accounts to join the organization
- B. Create an SCP that has full administrative privilege
- C. Attach the SCP to the management account.
- D. Invite the acquired company's AWS accounts to join the organization
- E. Create the OrganizationAccountAccessRole IAM role in the invited account
- F. Grant permission to the management account to assume the role.
- G. Use AWS Security Hub to collect and group findings across all accounts
- H. Use Security Hub to automatically detect new accounts as the accounts are added to the organization.
- I. Use AWS Firewall Manager to collect and group findings across all accounts
- J. Enable all features for the organization
- K. Designate an account in the organization as the delegated administrator account for Firewall Manager.
- L. Use Amazon Inspector to collect and group findings across all accounts
- M. Designate an account in the organization as the delegated administrator account for Amazon Inspector.

**Answer:** BC

#### Explanation:

The correct answer is B and C. Option B is correct because inviting the acquired company's AWS accounts to join the organization and creating the OrganizationAccountAccessRole IAM role in the invited accounts allows the management account to assume the role and gain full administrative access to the member accounts. Option C is correct because using AWS Security Hub to collect and group findings across all accounts enables the DevOps team to monitor and improve the security posture of the organization. Security Hub can automatically detect new accounts as the accounts are added to the organization and enable Security Hub for them. Option A is incorrect because creating an SCP that has full administrative privileges and attaching it to the management account does not grant the management account access to the member accounts. SCPs are used to restrict the permissions of the member accounts, not to grant permissions to the management account. Option D is incorrect because using AWS Firewall Manager to collect and group findings across all accounts is not a valid use case for Firewall Manager. Firewall Manager is used to centrally configure and manage firewall rules across the organization, not to collect and group security findings. Option E is incorrect because using Amazon Inspector to collect and group findings across all accounts is not a valid use case for Amazon Inspector. Amazon Inspector is used to assess the security and compliance of applications running on Amazon EC2 instances, not to collect and group security findings across accounts. References:

- ? Inviting an AWS account to join your organization
- ? Enabling and disabling AWS Security Hub
- ? Service control policies
- ? AWS Firewall Manager
- ? Amazon Inspector

#### NEW QUESTION 127

A development team uses AWS CodeCommit, AWS CodePipeline, and AWS CodeBuild to develop and deploy an application. Changes to the code are submitted by pull requests. The development team reviews and merges the pull requests, and then the pipeline builds and tests the application.

Over time, the number of pull requests has increased. The pipeline is frequently blocked because of failing tests. To prevent this blockage, the development team wants to run the unit and integration tests on each pull request before it is merged.

Which solution will meet these requirements?

- A. Create a CodeBuild project to run the unit and integration test
- B. Create a CodeCommit approval rule template
- C. Configure the template to require the successful invocation of the CodeBuild project
- D. Attach the approval rule to the project's CodeCommit repository.
- E. Create an Amazon EventBridge rule to match pullRequestCreated events from CodeCommit. Create a CodeBuild project to run the unit and integration test
- F. Configure the CodeBuild project as a target of the EventBridge rule that includes a custom event payload with the CodeCommit repository and branch information from the event.
- G. Create an Amazon EventBridge rule to match pullRequestCreated events from CodeCommit
- H. Modify the existing CodePipeline pipeline to not run the deploy steps if the build is started from a pull request
- I. Configure the EventBridge rule to run the pipeline with a custom payload that contains the CodeCommit repository and branch information from the event.
- J. Create a CodeBuild project to run the unit and integration test
- K. Create a CodeCommit notification rule that matches when a pull request is created or updated
- L. Configure the notification rule to invoke the CodeBuild project.

**Answer:** B

#### Explanation:

CodeCommit generates events in CloudWatch, CloudWatch triggers the CodeBuild <https://aws.amazon.com/es/blogs/devops/complete-ci-cd-with-aws-codecommit-aws-codebuild-aws-codedeploy-and-aws-codepipeline/>

#### NEW QUESTION 130

A company is developing an application that will generate log events. The log events consist of five distinct metrics every one tenth of a second and produce a large amount of data. The company needs to configure the application to write the logs to Amazon Time Stream. The company will configure a daily query against the Timestream table.

Which combination of steps will meet these requirements with the FASTEST query performance? (Select THREE.)

- A. Use batch writes to write multiple log events in a single write operation
- B. Write each log event as a single write operation

- C. Treat each log as a single-measure record
- D. Treat each log as a multi-measure record
- E. Configure the memory store retention period to be longer than the magnetic store retention period
- F. Configure the memory store retention period to be shorter than the magnetic store retention period

**Answer:** ADF

**Explanation:**

A comprehensive and detailed explanation is:

? Option A is correct because using batch writes to write multiple log events in a single write operation is a recommended practice for optimizing the performance and cost of data ingestion in Timestream. Batch writes can reduce the number of network round trips and API calls, and can also take advantage of parallel processing by Timestream. Batch writes can also improve the compression ratio of data in the memory store and the magnetic store, which can reduce the storage costs and improve the query performance<sup>1</sup>.

? Option B is incorrect because writing each log event as a single write operation is not a recommended practice for optimizing the performance and cost of data ingestion in Timestream. Writing each log event as a single write operation would increase the number of network round trips and API calls, and would also reduce the compression ratio of data in the memory store and the magnetic store. This would increase the storage costs and degrade the query performance<sup>1</sup>.

? Option C is incorrect because treating each log as a single-measure record is not a recommended practice for optimizing the query performance in Timestream. Treating each log as a single-measure record would result in creating multiple records for each timestamp, which would increase the storage size and the query latency. Moreover, treating each log as a single-measure record would require using joins to query multiple measures for the same timestamp, which would add complexity and overhead to the query processing<sup>2</sup>.

? Option D is correct because treating each log as a multi-measure record is a recommended practice for optimizing the query performance in Timestream. Treating each log as a multi-measure record would result in creating a single record for each timestamp, which would reduce the storage size and the query latency. Moreover, treating each log as a multi-measure record would allow querying multiple measures for the same timestamp without using joins, which would simplify and speed up the query processing<sup>2</sup>.

? Option E is incorrect because configuring the memory store retention period to be longer than the magnetic store retention period is not a valid option in Timestream. The memory store retention period must always be shorter than or equal to the magnetic store retention period. This ensures that data is moved from the memory store to the magnetic store before it expires out of the memory store<sup>3</sup>.

? Option F is correct because configuring the memory store retention period to be shorter than the magnetic store retention period is a valid option in Timestream. The memory store retention period determines how long data is kept in the memory store, which is optimized for fast point-in-time queries. The magnetic store retention period determines how long data is kept in the magnetic store, which is optimized for fast analytical queries. By configuring these retention periods appropriately, you can balance your storage costs and query performance according to your application needs<sup>3</sup>.

References:

? 1: Batch writes

? 2: Multi-measure records vs. single-measure records

? 3: Storage

**NEW QUESTION 134**

.....

## **Thank You for Trying Our Product**

### **We offer two products:**

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### **DOP-C02 Practice Exam Features:**

- \* DOP-C02 Questions and Answers Updated Frequently
- \* DOP-C02 Practice Questions Verified by Expert Senior Certified Staff
- \* DOP-C02 Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* DOP-C02 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The DOP-C02 Practice Test Here](#)**