

Exam Questions NSE7_SDW-7.0

Fortinet NSE 7 - SD-WAN 7.0

https://www.2passeasy.com/dumps/NSE7_SDW-7.0/



NEW QUESTION 1

Which diagnostic command can you use to show the member utilization statistics measured by performance SLAs for the last 10 minutes?

- A. diagnose sys sdwan intf-sla-log
- B. diagnose sys sdwan health-check
- C. diagnose sys sdwan log
- D. diagnose sys sdwan sla-log

Answer: D

Explanation:

SD-WAN 7.2 Study Guide page 321 You can view the stored member metrics by running the diagnose sys sdwan sla-log command. Note that you must include the name of the performance SLA followed by the member configuration index number. To display the SLA logs per interface, you run the diagnose sys sdwan intf-sla-log command.

NEW QUESTION 2

Which are two benefits of using CLI templates in FortiManager? (Choose two.)

- A. You can reference meta fields.
- B. You can configure interfaces as SD-WAN members without having to remove references first.
- C. You can configure FortiManager to sync local configuration changes made on the managed device, to the CLI template.
- D. You can configure advanced CLI settings.

Answer: AD

NEW QUESTION 3

Refer to the exhibit.

```
config system virtual-wan-link
  set status enable
  set load-balance-mode source-ip-based
  config members
    edit 1
      set interface "port1"
      set gateway 100.64.1.254
      set source 100.64.1.1
      set cost 15
    next
    edit 2
      set interface "port2"
      set gateway 100.64.2.254
      set priority 10
    next
  end
end
```

Based on the output shown in the exhibit, which two criteria on the SD-WAN member configuration can be used to select an outgoing interface in an SD-WAN rule? (Choose two.)

- A. Set priority 10.
- B. Set cost 15.
- C. Set load-balance-mode source-ip-ip-based.
- D. Set source 100.64.1.1.

Answer: AB

NEW QUESTION 4

Refer to the exhibit.

```
ike 0:T_INET_0_0:214: received informational request
ike 0:T_INET_0_0:214: processing notify type SHORTCUT_QUERY
ike 0:T_INET_0_0: recv shortcut-query 9065761962601467474
07409008f7fbd17e/0000000000000000 192.2.0.1 10.0.1.101->10.0.2.101 psk 64 ppk 0 ttl 32
nat 0 ver 2 mode 0
ike 0:T_INET_0: iif 20 10.0.1.101->10.0.2.101 route lookup oif 20 T_INET_0 gwy
10.201.1.1
ike 0:T_INET_0_1: forward shortcut-query 9065761962601467474
07409008f7fbd17e/0000000000000000 192.2.0.1 10.0.1.101->10.0.2.101 psk 64 ppk 0 ttl 31
ver 2 mode 0, ext-mapping 192.2.0.1:500
```

Which statement about the role of the ADVPN device in handling traffic is true?

- A. This is a spoke that has received a query from a remote hub and has forwarded the response to its hub.
- B. Two hubs, 10.0.1.101 and 10.0.2.101, are receiving and forwarding queries between each other.
- C. This is a hub that has received a query from a spoke and has forwarded it to another spoke.
- D. Two spokes, 192.2.0.1 and 10.0.2.101, forward their queries to their hubs.

Answer: C

NEW QUESTION 5

What is a benefit of using application steering in SD-WAN?

- A. The traffic always skips the regular policy routes.
- B. You steer traffic based on the detected application.
- C. You do not need to enable SSL inspection.
- D. You do not need to configure firewall policies that accept the SD-WAN traffic.

Answer: B

NEW QUESTION 6

Which are three key routing principles in SD-WAN? (Choose three.)

- A. FortiGate performs route lookups for new sessions only.
- B. Regular policy routes have precedence over SD-WAN rules.
- C. SD-WAN rules have precedence over ISDB routes.
- D. By default, SD-WAN members are skipped if they do not have a valid route to the destination.
- E. By default, SD-WAN rules are skipped if the best route to the destination is not an SD-WAN member.

Answer: BDE

NEW QUESTION 7

Which two statements are correct when traffic matches the implicit SD-WAN rule? (Choose two.)

- A. The `sdwan_service_id` flag in the session information is 0.
- B. All SD-WAN rules have the default setting enabled.
- C. Traffic does not match any of the entries in the policy route table.
- D. Traffic is load balanced using the algorithm set for the `v4-ecmp-mode` setting.

Answer: AC

Explanation:

`sdwan_service_id` is 0 = match SD-WAN implicit rule, study guide 7.0 page 120, 7.2 page 149 SD-WAN rules internally are interpreted as a Policy route, so when the traffic doesn't match with any policy route, it will be flowing by implicit policy.

NEW QUESTION 8

Refer to the exhibits.

Exhibit A

```
branch1_fgt # diagnose sys sdwan service

Service(1): Address Mode(IPV4) flags=0x200 use-shortcut-sla
  Gen(8), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(manual)
  Members(2):
    1: Seq_num(1 port1), alive, selected
    2: Seq_num(2 port2), alive, selected
  Internet Service(3): GoToMeeting(4294836966,0,0,0 16354)
  Microsoft.Office.365.Portal(4294837474,0,0,0 41468) Salesforce(4294837976,0,0,0 16920)
  Src address(1):
    10.0.1.0-10.0.1.255

Service(2): Address Mode(IPV4) flags=0x200 use-shortcut-sla
  Gen(7), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(manual)
  Members(1):
    1: Seq_num(2 port2), alive, selected
  Internet Service(2): Facebook(4294836806,0,0,0 15832) Twitter(4294838278,0,0,0 16001)
  Src address(1):
    10.0.1.0-10.0.1.255

branch1_fgt # diagnose sys sdwan internet-service-app-ctrl-list

Facebook(15832 4294836806): 157.240.229.35 6 443 Tue Mar  8 12:24:04 2022
GoToMeeting(16354 4294836966): 23.205.106.86 6 443 Tue Mar  8 12:24:04 2022
GoToMeeting(16354 4294836966): 23.212.249.144 6 443 Tue Mar  8 12:24:39 2022
Salesforce(16920 4294837976): 23.212.249.11 6 443 Tue Mar  8 12:24:04 2022

branch1_fgt # get router info routing-table all
...
S*      0.0.0.0/0 [1/0] via 192.2.0.2, port1
        [1/0] via 192.2.0.10, port2
...
```

Exhibit B

Destination IP	Service	Application	Security Event List	SD-WAN Rule Name	Destination Interface
23.212.248.205	HTTPS	GoToMeeting	APP: 2		port2
23.205.106.86	HTTPS	GoToMeeting	APP: 2	Critical-DIA	port1
23.205.106.86	HTTPS	GoToMeeting	APP: 2	Critical-DIA	port1
23.205.106.86	HTTPS	GoToMeeting	APP: 2	Critical-DIA	port1
23.212.249.144	HTTPS	GoToMeeting	APP: 2	Critical-DIA	port1
23.212.249.144	HTTPS	GoToMeeting	APP: 2		port1
23.212.249.144	HTTPS	GoToMeeting	APP: 2		port2
23.205.106.86	HTTPS	GoToMeeting	APP: 2		port2

Security	APP Count	2
Level	notice	
General	Log ID	000000013
Session ID	769	
Tran Display	snat	
Virtual Domain	root	
Source	Country	Reserved
Device ID	FGVM01TM22000077	
Device Name	branch1_fgt	
IP	10.0.1.101	
Interface	port5	
Interface Role	undefined	
NAT IP	192.2.0.9	
NAT Port	51042	
Port	51042	
Source	10.0.1.101	
UEBA Endpoint ID	1025	
UEBA User ID	3	
Destination	Country	United States
End User ID	3	
Endpoint ID	101	
Host Name	www.gotomeeting.com	
IP	23.212.248.205	
Interface	port2	

An administrator is testing application steering in SD-WAN. Before generating test traffic, the administrator collected the information shown in exhibit A. After generating GoToMeeting test traffic, the administrator examined the respective traffic log on FortiAnalyzer, which is shown in exhibit B. The administrator noticed that the traffic matched the implicit SD-WAN rule, but they expected the traffic to match rule ID 1.

Which two reasons explain why the traffic matched the implicit SD-WAN rule? (Choose two.)

- A. FortiGate did not refresh the routing information on the session after the application was detected.
- B. Port1 and port2 do not have a valid route to the destination.
- C. Full SSL inspection is not enabled on the matching firewall policy.
- D. The session 3-tuple did not match any of the existing entries in the ISDB application cache.

Answer: AC

NEW QUESTION 9

Which two statements about the SD-WAN zone configuration are true? (Choose two.)

- A. The service-sla-tie-break setting enables you to configure preferred member selection based on the best route to the destination.
- B. You can delete the default zones.
- C. The default zones are virtual-wan-link and SASE.
- D. An SD-WAN member can belong to two or more zones.

Answer: AC

NEW QUESTION 10

Refer to the exhibits. Exhibit A

```
config system sdwan
  config health-check
    edit "Passive"
      set detect-mode passive
      set members 3 4
    next
  end
end

config system sdwan
  config service
    edit 1
      set name "Facebook-YouTube"
      set src "all"
      set internet-service enable
      set internet-service-app-ctrl 15832 31077
      set health-check "Passive"
      set priority-member 3 4
      set passive-measurement enable
    next
  end
end

branch1_fgt # get application name status | grep "id: 15832" -B1
app-name: "Facebook"
id: 15832

branch1_fgt # get application name status | grep "id: 31077" -B1
app-name: "YouTube"
id: 31077
```

Exhibit B

```
config firewall policy
  edit 1
    set name "DIA"
    set uuid b973e4ec-5f90-51ec-cadb-017c830d9418
    set srcintf "port5"
    set dstintf "underlay"
    set action accept
    set srcaddr "LAN-net"
    set dstaddr "all"
    set schedule "always"
    set service "ALL"
    set passive-wan-health-measurement enable
    set utm-status enable
    set ssl-ssh-profile "certificate-inspection"
    set application-list "default"
    set logtraffic all
    set auto-asic-offload disable
    set nat enable
  next
end

branch1_fgt # diagnose sys sdwan zone | grep underlay -A1
Zone underlay index=3
  members(2): 3(port1) 4(port2)
```

Exhibit A shows the SD-WAN performance SLA configuration, the SD-WAN rule configuration, and the application IDs of Facebook and YouTube. Exhibit B shows the firewall policy configuration and the underlay zone status.

Based on the exhibits, which two statements are correct about the health and performance of port1 and port2? (Choose two.)

- A. The performance is an average of the metrics measured for Facebook and YouTube traffic passing through the member.
- B. FortiGate is unable to measure jitter and packet loss on Facebook and YouTube traffic.
- C. FortiGate identifies the member as dead when there is no Facebook and YouTube traffic passing through the member.
- D. Non-TCP Facebook and YouTube traffic are not used for performance measurement.

Answer: AD

Explanation:

Study Guide 7.0, pages 88 - 89.

Study Guide 7.2, pages 103 - 104.

Another comment said "because without using application Control on the firewall policy, SDWAN can't work" but there is a app control "default" defined on config.

NEW QUESTION 10

Refer to the exhibit.

The screenshot shows the 'Create New SD-WAN Interface Member' configuration page. The fields are as follows:

Field	Value
Sequence Number	1
Interface Member	
SD-WAN Zone	virtual-wan-link
Gateway IP	0.0.0.0
Cost	0
Status	<input checked="" type="checkbox"/>
Priority	0

Advanced Options >

Which two SD-WAN template member settings support the use of FortiManager meta fields? (Choose two.)

- A. Cost
- B. Interface member
- C. Priority
- D. Gateway IP

Answer: BD

NEW QUESTION 12

What are two benefits of using forward error correction (FEC) in IPsec VPNs? (Choose two.)

- A. FEC supports hardware offloading.
- B. FEC improves reliability of noisy links.
- C. FEC transmits parity packets that can be used to reconstruct packet loss.
- D. FEC can leverage multiple IPsec tunnels for parity packets transmission.

Answer: BC

NEW QUESTION 17

Which two statements about SD-WAN central management are true? (Choose two.)

- A. The objects are saved in the ADOM common object database.
- B. It does not support meta fields.
- C. It uses templates to configure SD-WAN on managed devices.
- D. It supports normalized interfaces for SD-WAN member configuration.

Answer: AC

Explanation:

Normalized interfaces are not supported for SD-WAN templates. You can create multiple SD-WAN zones and add interface members to the SD-WAN zones. You must bind the interface members by name to physical interfaces or VPN interfaces. <https://docs.fortinet.com/document/fortigate/7.0.0/sd-wan-new-features/794804/new-sd-wan-template>

NEW QUESTION 22

Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 1

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
Gen(6), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(manual)
Members(2):
  1: Seq_num(3 T_INET_0_0), alive, selected
  2: Seq_num(4 T_INET_1_0), alive, selected
Src address(1):
  10.0.1.0-10.0.1.255

Dst address(1):
  10.0.0.0-10.255.255.255

branch1_fgt # diagnose sys sdwan member | grep T_INET_
Member(3): interface: T_INET_0_0, flags=0x4 , gateway: 100.64.1.1, priority: 10 1024,
weight: 0
Member(4): interface: T_INET_1_0, flags=0x4 , gateway: 100.64.1.9, priority: 0 1024,
weight: 0

branch1_fgt # get router info routing-table all | grep T_INET_
S      10.0.0.0/8 [1/0] via T_INET_1_0 tunnel 100.64.1.9
```

An administrator is troubleshooting SD-WAN on FortiGate. A device behind branch1_fgt generates traffic to the 10.0.0.0/8 network. The administrator expects the traffic to match SD-WAN rule ID 1 and be routed over T_INET_0_0. However, the traffic is routed over T_INET_1_0. Based on the output shown in the exhibit, which two reasons can cause the observed behavior? (Choose two.)

- A. The traffic matches a regular policy route configured with T_INET_1_0 as the outgoing device.
- B. T_INET_1_0 has a lower route priority value (higher priority) than T_INET_0_0.
- C. T_INET_0_0 does not have a valid route to the destination.
- D. T_INET_1_0 has a higher member configuration priority than T_INET_0_0.

Answer: AC

Explanation:

<https://community.fortinet.com/t5/FortiGate/Technical-Tip-Assigning-Priority-to-SD-WAN-Members-for-Defau>

NEW QUESTION 24

Refer to the exhibit.

```
config vpn ipsec phase1-interface
edit "FIRST_VPN"
  set type dynamic
  set interface "port1"
  set peertype any
  set proposal aes128-sha256 aes256-sha38
  set dhgrp 14 15 19
  set xauthtype auto
  set authusrgrp "first-group"
  set psksecret fortinet1
next
edit "SECOND_VPN"
  set type dynamic
  set interface "port1"
  set peertype any
  set proposal aes128-sha256 aes256-sha38
  set dhgrp 14 15 19
  set xauthtype auto
  set authusrgrp "second-group"
  set psksecret fortinet2
next
edit
```

FortiGate has multiple dial-up VPN interfaces incoming on port1 that match only FIRST_VPN.

Which two configuration changes must be made to both IPsec VPN interfaces to allow incoming connections to match all possible IPsec dial-up interfaces? (Choose two.)

- A. Specify a unique peer ID for each dial-up VPN interface.
- B. Use different proposals are used between the interfaces.
- C. Configure the IKE mode to be aggressive mode.
- D. Use unique Diffie Hellman groups on each VPN interface.

Answer: AC

NEW QUESTION 25

Which two statements are true about using SD-WAN to steer local-out traffic? (Choose two.)

- A. FortiGate does not consider the source address of the packet when matching an SD-WAN rule for local-out traffic.
- B. By default, local-out traffic does not use SD-WAN.
- C. By default, FortiGate does not check if the selected member has a valid route to the destination.
- D. You must configure each local-out feature individually, to use SD-WAN.

Answer: BD

NEW QUESTION 29

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual NSE7_SDW-7.0 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the NSE7_SDW-7.0 Product From:

https://www.2passeasy.com/dumps/NSE7_SDW-7.0/

Money Back Guarantee

NSE7_SDW-7.0 Practice Exam Features:

- * NSE7_SDW-7.0 Questions and Answers Updated Frequently
- * NSE7_SDW-7.0 Practice Questions Verified by Expert Senior Certified Staff
- * NSE7_SDW-7.0 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * NSE7_SDW-7.0 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year