

Exam Questions EX200

EX200 Red Hat Certified System Administrator (RHCSA) Exam

<https://www.2passeasy.com/dumps/EX200/>



NEW QUESTION 1

Configure a cron Task.

User natasha must configure a cron job, local time 14:23 runs and executes: */bin/echo hiya every day.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
crontab -e -u natasha 23 14/bin/echo hiya
crontab -l -u natasha // view systemctl enable crond systemctl restart crond
```

NEW QUESTION 2

SELinux must run in force mode.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
/etc/sysconfig/selinux
SELINUX=enforcing
```

NEW QUESTION 3

Install a FTP server, and request to anonymous download from /var/ftp/pub catalog. (it needs you to configure yum direct to the already existing file server.)

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# cd /etc/yum.repos.d
# vim local.repo
[local]
name=local.repo
baseurl=file:///mnt
enabled=1
gpgcheck=0
# yum makecache
# yum install -y vsftpd
# service vsftpd restart
# chkconfig vsftpd on
# chkconfig --list vsftpd
# vim /etc/vsftpd/vsftpd.conf
anonymous_enable=YES
```

NEW QUESTION 4

Set cronjob for user natasha to do /bin/echo hiya at 14:23.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# crontab -e -u natasha
23 14 * * * /bin/echo hiya
wq!
```

NEW QUESTION 5

Configure the FTP service in your system, allow remote access to anonymous login and download the program by this service. Service is still running after system rebooting.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
yum install vsftpd
/etc/init.d/vsftpd start
chkconfig vsftpd on
```

NEW QUESTION 6

Configure the verification mode of your host account and the password as LDAP. And it can login successfully through ldapuser40. The password is set as "password".
And the certificate can be downloaded from <http://ip/dir/ldap.crt>. After the user logs on the user has no host directory unless you configure the autofs in the following questions.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
system-config-authentication
LDAP Server: ldap://instructor.example.com (In domain form, not write IP)
OR
# yum groupinstall directory-client (1.krb5-workstation 2.pam-krb5 3.sssd)
# system-config-authentication
1.User Account Database: LDAP
2. LDAP Search Base DN: dc=example,dc=com
3. LDAP Server: ldap://instructor.example.com (In domain form, not write IP)
4. Download CA Certificate
5. Authentication Method: LDAP password
6. Apply
getent passwd ldapuser40
```

NEW QUESTION 7

Your System is going to use as a Router for two networks. One Network is 192.168.0.0/24 and Another Network is 192.168.1.0/24. Both network's IP address has assigned. How will you forward the packets from one network to another network?

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
echo "1" >/proc/sys/net/ipv4/ip_forward
vi /etc/sysctl.conf
net.ipv4.ip_forward = 1
```

If you want to use the Linux System as a Router to make communication between different networks, you need enable the IP forwarding. To enable on running session just set value 1 to `/proc/sys/net/ipv4/ip_forward`. As well as automatically turn on the IP forwarding features on next boot set on `/etc/sysctl.conf` file.

NEW QUESTION 8

Configure autofs to make sure after login successfully, it has the home directory autofs, which is shared as `/rhome/ldapuser40` at the ip: 172.24.40.10. and it also requires that, other ldap users can use the home directory normally.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# chkconfig autofs on
# cd /etc/
# vim /etc/auto.master
/rhome /etc/auto.ldap
# cp auto.misc auto.ldap
# vim auto.ldap
ldapuser40 -rw,soft,intr 172.24.40.10:/rhome/ldapuser40
* -rw,soft,intr 172.16.40.10:/rhome/&
# service autofs stop
# server autofs start
# showmount -e 172.24.40.10
# su - ldapuser40
```

NEW QUESTION 9

Who ever creates the files/directories on a data group owner should automatically be in the same group owner as data.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
1. chmod g+s /data
2. Verify using: ls -ld /data
```

Permission should be like this: drwxrws--- 2 root sysadmin 4096 Mar 16 18:08 /data

If SGID bit is set on directory then who every users creates the files on directory group owner automatically the owner of parent directory. To set the SGID bit: chmod g+s directory To Remove the SGID bit: chmod g-s directory

NEW QUESTION 10

Create a 2G swap partition which take effect automatically at boot-start, and it should not affect the original swap partition.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# fdisk /dev/sda
p
(check Partition table)
n
(create new partition: press e to create extended partition, press p to create the main partition, and the extended partition is further divided into logical partitions)
Enter
+2G t
8 l
82
W
partx -a /dev/sda
partprobe
mkswap /dev/sda8
Copy UUID
swapon -a
vim /etc/fstab
UUID=XXXXXX swap swap defaults 0 0
(swapon -s)
```

NEW QUESTION 10

You are a System administrator. Using Log files very easy to monitor the system. Now there are 50 servers running as Mail, Web, Proxy, DNS services etc. You want to centralize the logs from all servers into on LOG Server. How will you configure the LOG Server to accept logs from remote host?

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

By default, system accept the logs only generated from local host. To accept the Log from other host configure:

```
vi /etc/sysconfig/syslog SYSLOGD_OPTIONS="-m 0 -r"
```

Where

-m 0 disables 'MARK' messages.

-r enables logging from remote machines

-x disables DNS lookups on messages received with -r
service syslog restart

NEW QUESTION 15

Find all lines in the file /usr/share/dict/words that contain the string seismic. Put a copy of all these lines in their original order in the file /root/wordlist. /root/wordlist should contain no empty lines and all lines must be exact copies of the original lines in /usr/share/dict/words.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
grep seismic /usr/share/dict/words> /root/wordlist
```

NEW QUESTION 19

Configure your Host Name, IP Address, Gateway and DNS.

Host name: dtop5.dn.ws.com

IP Address: 172.28.10.5/4


Gateway: 172.28.10.1

DNS: 172.28.10.1

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

 Configure Host Name

 vim /etc/sysconfig/network NETWORKING=yes HOSTNAME=dtop5.dn.ws.com GATEWAY=172.28.10.1

2. Configure IP Address, Gateway and DNS
Configure the network by Network Manager:

Editing System eth0

Connection name: System eth0

☒ Connect automatically

Wired 802.1x Security IPv4 Settings IPv6 Settings

Method: Manual

Addresses

Address	Netmask	Gateway
172.28.10.5	255.255.255.0	172.28.10.1

DNS servers: 172.28.10.1

Search domains: dn.ws.com

DHCP client ID:

☒ Require IPv4 addressing for this connection to complete

Routes...

☒ Available to all users

Cancel Apply...

Note: Please remember to choose two options:

- ☒ Connect automatically
- ☒ Available to all users

Click "Apply", save and exit, and restart your network services:

Service network restart

3. Validate these profiles:

a) Check gateway: # vim / etc / sysconfig / network

NETWORKING=yes

HOSTNAME=dtop5.dn.ws.com

GATEWAY=172.28.10.1

b) Check Host Name: # vim /etc/hosts

```
172.28.10.5 dtop5.dn.ws.com dtop5 # Added by NetworkManager
127.0.0.1 localhost.localdomain localhost
::1 dtop.dn.ws.com dtop5 localhost6.localdomain6 localhost6
```

c) Check DNS: # vim /etc/resolv.conf

Generated by NetworkManager

Search dn.ws.com

Nameserver 172.28.10.1

d) Check Gateway: # vim /etc/sysconfig/network-scripts/ifcfg-eth0


```
DEVICE="eth0"
NM_CONTROLLED="yes"
ONBOOT=yes
TYPE=Ethernet
BOOTPROTO=none
IPADDR=172.28.10.5
PREFIX=24
GATEWAY=172.28.10.1
DNS1=172.28.10.1
DOMAIN=dn.ws.com
DEFROUTE=yes
IPV4_FAILURE_FATAL=yes
IPV6INIT=no
NAME="System eth0"
UUID=5fb06bd0-0bb0-7ffb-45f1-d6edd65f3e03
HWADDR=00:0c:29:0E:A6:C8
```

NEW QUESTION 23

SIMULATION

Add an additional swap partition of 754 MB to your system.

The swap partition should automatically mount when your system boots.

Do not remove or otherwise alter any existing swap partitions on your system.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
❖ fdisk -l
❖ fdisk -cu /dev/vda
p n
e or p select e
default (first): enter
default (last): enter n
default(first): enter
default(first): +754M t (1-5)
1: 82 p
w #reboot
#mkswap /dev/vda5
❖ vim /etc/fstab
/dev/vda5 swap swap defaults 0 0
wq
❖ mount -a
❖ swapon -a
❖ swapon -s
```

NEW QUESTION 28

Find the files owned by harry, and copy it to catalog: /opt/dir

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# cd /opt/
# mkdir dir
```

```
# find / -user harry -exec cp -rfp {} /opt/dir/ \;
```

NEW QUESTION 33

Configure iptables, there are two domains in the network, the address of local domain is 172.24.0.0/16 other domain is 172.25.0.0/16, now refuse domain 172.25.0.0/16 to access the server.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

below

- ▶ iptables -F
- ▶ service iptables save
- ▶ iptables -A INPUT -s 172.25.0.0/16 -j REJECT
- ▶ service iptables save
- ▶ service iptables restart

NEW QUESTION 37

Please open the ip_forward, and take effect permanently.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

- ▶ vim /etc/sysctl.conf net.ipv4.ip_forward = 1
- ▶ sysctl -w (takes effect immediately)

If no “sysctl.conf” option, use these commands:

- ▶ sysctl -a |grep net.ipv4
- ▶ sysctl -P net.ipv4.ip_forward = 1
- ▶ sysctl -w

NEW QUESTION 42

Some users home directory is shared from your system. Using showmount -e localhost command, the shared directory is not shown. Make access the shared users home directory.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

- ▶ Verify the File whether Shared or not ? : cat /etc/exports
- ▶ Start the nfs service: service nfs start
- ▶ Start the portmap service: service portmap start
- ▶ Make automatically start the nfs service on next reboot: chkconfig nfs on
- ▶ Make automatically start the portmap service on next reboot: chkconfig portmap on
- ▶ Verify either sharing or not: showmount -e localhost
- ▶ Check that default firewall is running on system?

If running flush the iptables using iptables -F and stop the iptables service.

NEW QUESTION 47

According the following requirements, configure autofs service and automatically mount to user's home directory in the ldap domain.

- Instructor.example.com (192.168.0.254) has shared /home/guests/ldapuserX home directory to your system by over NFS export, X is your hostname number.
- LdapuserX's home directory is exist in the instructor.example.com: /home/ guests/ldapuserX
- LdapuserX's home directory must be able to automatically mount to /home/ guests/ldapuserX in your system.
- Home directory have write permissions for the corresponding user.

However, you can log on to the ldapuser1 - ldapuser99 users after verification. But you can only get your corresponding ldapuser users. If your system's hostname is server1.example.com, you can only get ldapuser1's home directory.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

(1)find /etc -size 10k -exec cp {} /tmp/findfiles \;
(2)find / -user lucy -exec cp -a {} /tmp/findfiles \;

Note: If find users and permissions, you need to use cp - a options, to keep file permissions and user attributes etc.

NEW QUESTION 52

Search a String

Find out all the columns that contains the string seismic within /usr/share/dict/words, then copy all these columns to /root/lines.tx in original order, there is no blank line, all columns must be the accurate copy of the original columns.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
grep seismic /usr/share/dict/words> /root/lines.txt
```

NEW QUESTION 54

Create a user named alex, and the user id should be 1234, and the password should be alex111.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# useradd -u 1234 alex
# passwd alex
alex111
alex111
OR
echo alex111|passwd -stdin alex
```

NEW QUESTION 58

According the following requirements to create a local directory /common/admin.

- ☒ This directory has admin group.
- ☒ This directory has read, write and execute permissions for all admin group members.
- ☒ Other groups and users don't have any permissions.
- ☒ All the documents or directories created in the/common/admin are automatically inherit the admin group.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
mkdir -p /common/admin
chgrp admin /common/admin
chmod 2770 /common/admin
```

NEW QUESTION 61

Upgrading the kernel as 2.6.36.7.1, and configure the system to Start the default kernel, keep the old kernel available.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# cat /etc/grub.conf
# cd /boot
# lftp it
# get dr/dom/kernel-xxxx.rpm
# rpm -ivh kernel-xxxx.rpm
# vim /etc/grub.conf default=0
```

NEW QUESTION 64

Configure a task: plan to run echo hello command at 14:23 every day.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:


```
# which echo
# crontab -e
23 14 * * * /bin/echo hello
# crontab -l (Verify)
```

NEW QUESTION 66

Open kmcrl value of 5 , and can verify in /proc/ cmdline

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

see explanation below.

```
# vim /boot/grub/grub.conf
kernel/vmlinuz-2.6.32-71.el6.x86_64 ro root=/dev/mapper/GLSvg-GLSrootrd_LVM_LV=GLSvg/GLSroot
rd_LVM_LV=GLSvg/GLSswaprd_NO_LUKSrd_NO_MDrd_NO_DM
LANG=en_US.UTF-8 SYSFONT=latacyrheb-sun16 KEYBOARDTYPE=pc KEYTABLE=us crashkernel=auto rhgb quiet kmcrl=5
Restart to take effect and verification:
# cat /proc/cmdline
ro root=/dev/mapper/GLSvg-GLSroot rd_LVM_LV=GLSvg/GLSroot rd_LVM_LV=GLSvg/GLSswap rd_NO_LUKS rd_NO_MD rd_NO_DM
LANG=en_US.UTF-8 SYSFONT=latacyrheb-sun16 KEYBOARDTYPE=pc KEYTABLE=us rhgb quiet kmcrl=5
```

NEW QUESTION 67

A YUM source has been provided in the <http://instructor.example.com/pub/rhel6/dvd>
Configure your system and can be used normally.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
▶ /etc/yum.repos.d/base.repo
[base]
name=base
baseurl=http://instructor.example.com/pub/rhel6/dvd
gpgcheck=0
yum list
```

NEW QUESTION 71

Create a volume group, and set 16M as a extends. And divided a volume group containing 50 extends on volume group lv, make it as ext4 file system, and mounted automatically under /mnt/data.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# pvcreate /dev/sda7 /dev/sda8
# vgcreate -s 16M vg1 /dev/sda7 /dev/sda8
# lvcreate -l 50 -n lvm02
# mkfs.ext4 /dev/vg1/lvm02
# blkid /dev/vg1/lv1
# vim /etc/fstab
# mkdir -p /mnt/data
UUID=xxxxxxx /mnt/data ext4 defaults 0 0
# vim /etc/fstab
# mount -a
# mount
(Verify)
```

NEW QUESTION 75

Create a 2G swap partition which take effect automatically at boot-start, and it should not affect the original swap partition.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# fdisk /dev/sda
p
(check Partition table)
n
(create new partition: press e to create extended partition, press p to create the main partition, and the extended partition is further divided into logical partitions)
```

```
Enter
+2G
t
l
W
partx -a /dev/sda
partprobe
mkswap /dev/sda8
Copy UUID
swapon -a
vim /etc/fstab
UUID=XXXXXX swap swap defaults 0 0
(swapon -s)
```

NEW QUESTION 76

Add a swap partition.

Adding an extra 500M swap partition to your system, this swap partition should mount automatically when the system starts up. Don't remove and modify the existing swap partitions on your system.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

fdisk -cu /dev/vda// in the way of expanding the partition, don't make main partition

```
partx -a /dev/vda
mkswap /dev/vdax
swapon /dev/vdax
swapon -s
vi /etc/fstab
/dev/vdaxswapswapdefaults0 0
mount -a
```

NEW QUESTION 81

Create a volume group, and set the size is 500M, the size of single PE is 16M. Create logical volume named lv0 in this volume group, set size is 20 PE, make it as ext3 file system, and mounted automatically under data.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
fdisk /dev/vda
pvcreate /dev/vda3
vgcreate -s 16M vg0 /dev/vda3
lvcreate -n lv0 -l 20 vg0
mkfs.ext3 /dev/mapper/vg0-lv0
mkdir /data
/etc/fstab:
/dev/mapper/vg0-lv0 /data ext3 defaults 0 0
mount -a
mount | grep data
```

NEW QUESTION 84

The firewall must be open.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
/etc/init.d/iptables start
iptables -F
iptables -X
iptables -Z
/etc/init.d/iptables save
chkconfig iptables on
```

NEW QUESTION 88

Create one partitions having size 100MB and mount it on data.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

1. Use fdisk /dev/hda to create new partition.
2. Type n For New partitions.
3. It will ask for Logical or Primary Partitions. Press l for logical.
4. It will ask for the Starting Cylinder: Use the Default by pressing Enter Key.
5. Type the Size: +100M you can specify either Last cylinder of size here.
6. Press P to verify the partitions lists and remember the partitions name.
7. Press w to write on partitions table.
8. Either Reboot or use partprobe command.
9. Use mkfs -t ext3 /dev/hda?

OR

mkfs -t ext3 /dev/hda? To create ext3 filesystem.

vi /etc/fstab

Write:

/dev/hda? /data ext3 defaults 1 2

Verify by mounting on current Sessions also: mount /dev/hda? /data

NEW QUESTION 91

Search files.

Find out files owned by jack, and copy them to directory /root/findresults

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

mkdir /root/findfiles

find / -user jack -exec cp -a {} /root/findfiles/ \; ls /root/findresults

NEW QUESTION 94

There is a local logical volumes in your system, named with common and belong to VGSRV volume group, mount to the /common directory. The definition of size is 128 MB.

Requirement:

Extend the logical volume to 190 MB without any loss of data. The size is allowed between 160-160 MB after extending.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

lvextend -L 190M /dev/mapper/vgsrv-common resize2fs /dev/mapper/vgsrv-common

NEW QUESTION 99

One Logical Volume named /dev/test0/testvolume1 is created. The initial Size of that disk is 100MB now you required more 200MB. Increase the size of Logical Volume, size should be increase on online.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

 lvextend -L+200M /dev/test0/testvolume1 Use lvdisplay /dev/test0/testvolume1)

 ext2online -d /dev/test0/testvolume1

lvextend command is used the increase the size of Logical Volume. Other command lvresize command also here to resize. And to bring increased size on online we use the ext2online command.

NEW QUESTION 101


Make a swap partition having 100MB. Make Automatically Usable at System Boot Time.


- A. Mastered
- B. Not Mastered


Answer: A


Explanation:

see explanation below.

 Use fdisk /dev/hda ->To create new partition.

 Type n-> For New partition

 It will ask for Logical or Primary Partitions. Press l for logical.

 It will ask for the Starting Cylinder: Use the Default by pressing Enter Key.

 Type the Size: +100M ->You can Specify either Last cylinder of Size here.

- ▶ Press P to verify the partitions lists and remember the partitions name. Default System ID is 83 that means Linux Native.
- ▶ Type t to change the System ID of partition.
- ▶ Type Partition Number
- ▶ Type 82 that means Linux Swap.
- ▶ Press w to write on partitions table.
- ▶ Either Reboot or use partprobe command.
- ▶ mkswap /dev/hda? ->To create Swap File system on partition.
- ▶ swapon /dev/hda? ->To enable the Swap space from partition.
- ▶ free -m ->Verify Either Swap is enabled or not.
- ▶ vi /etc/fstab/dev/hda? swap swap defaults 0 0
- ▶ Reboot the System and verify that swap is automatically enabled or not.

NEW QUESTION 105

Create a collaborative directory/home/admins with the following characteristics: Group ownership of /home/admins is adminuser
The directory should be readable, writable, and accessible to members of adminuser, but not to any other user. (It is understood that root has access to all files and directories on the system.)
Files created in /home/admins automatically have group ownership set to the adminuser group

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
mkdir /home/admins
chgrp -R adminuser /home/admins
chmodg+w /home/admins
chmodg+s /home/admins
```

NEW QUESTION 106

Upgrade the kernel, start the new kernel by default. kernel download from this address: ftp://server1.domain10.example.com/pub/update/new.kernel

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
Download the new kernel file and then install it.
[root@desktop8 Desktop]# ls
kernel-2.6.32-71.7.1.el6.x86_64.rpm
kernel-firmware-2.6.32-71.7.1.el6.noarch.rpm
[root@desktop8 Desktop]# rpm -ivh kernel-*
Preparing... #####
[100%]
1:kernel-firmware
##### [ 50%]
2:kernel
##### [100%]
Verify the grub.conf file, whether use the new kernel as the default boot. [root@desktop8 Desktop]# cat
/boot/grub/grub.conf default=0
title Red Hat Enterprise Linux Server (2.6.32-71.7.1.el6.x86_64)
root (hd0,0)
kernel /vmlinuz-2.6.32-71.7.1.el6.x86_64 ro root=/dev/mapper/vol0-root rd_LVM_LV=vol0/root rd_NO_LUKS rd_NO_MD
rd_NO_DM LANG=en_US.UTF-8 SYSFONT=latarcyrheb-sun16 KEYBOARDTYPE=pc KEYTABLE=us crashkernel=auto rhgb quiet
initrd /initramfs-2.6.32-71.7.1.el6.x86_64.img
```

NEW QUESTION 107

Configure your system so that it is an NTP client of server.domain11.example.com

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
#system-config-date
Note: dialog box will open in that
Check mark Synchronize date and time over network. Remove all the NTP SERVER and click ADD and type server.domain11.example.com
*****And then press ENTER and the press OK*****
```

NEW QUESTION 112

There is a server having 172.24.254.254 and 172.25.254.254. Your System lies on 172.24.0.0/16. Make successfully ping to 172.25.254.254 by Assigning following IP: 172.24.0.x where x is your station number.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

- ▶ Use netconfig command
- ▶ Enter the IP Address as given station number by your examiner: example: 172.24.0.1
- ▶ Enter Subnet Mask
- ▶ Enter Default Gateway and primary name server
- ▶ press on ok
- ▶ ifdown eth0
- ▶ ifup eth0
- ▶ verify using ifconfig

In the lab server is playing the role of router, IP forwarding is enabled. Just set the Correct IP and gateway, you can ping to 172.25.254.254.

NEW QUESTION 115

SELinux must be running in the Enforcing mode.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
getenforce // Check the current mode of SELinux // SELinux runs in enforcing mode // Check
getenforce 1
getenforce
vim /etc/selinux/config selinux=enforcing // To temporarily enable SELinux
wg
sestatus
```

NEW QUESTION 117

Binding to an external validation server.

System server.domain11.example.com provides a LDAP validation service, your system should bind to this service as required:

Base DN of validation service is dc=example,dc=com

LDAP is used for providing account information and validation information Connecting and using the certification of

<http://server.domain11.example.com/pub/EXAMPLE-CA-CERT> to encrypt

After the correct configuration, ldapuser1 can log into your system, it does not have HOME directory until you finish autofs questions, ldapuser1 password is password.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
yum -y install sssd authconfig-gtk krb5-workstation authconfig-gtk // open the graphical interface
Modify user account database to ldap, fill up DN and LDAP SERVER as questions required, use TLS to encrypt connections making tick, write
http://server.domain11.example.com/pub/EXAMPLE-CA-CERT to download ca, authentication method choose ldap password.
You can test if the ldapuser is added by the following command:
Id ldapuser1
Note: user password doesn't not need to set
```

NEW QUESTION 119

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual EX200 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the EX200 Product From:

<https://www.2passeasy.com/dumps/EX200/>

Money Back Guarantee

EX200 Practice Exam Features:

- * EX200 Questions and Answers Updated Frequently
- * EX200 Practice Questions Verified by Expert Senior Certified Staff
- * EX200 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * EX200 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year