

# Cisco

## Exam Questions 300-610

Designing Cisco Data Center Infrastructure (DCID)



NEW QUESTION 1

Drag the requirements from the left onto the correct policy types on the right.

Support tagging policies.

Scrub disks on disassociation.

Synchronize server power state.

Create a utility partition on a SD card.

Implement Hypervisor password policies.

Cisco Intersight Global Policy

Cisco UCS Manager Local Policy

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Support tagging policies.

Scrub disks on disassociation.

Synchronize server power state.

Create a utility partition on a SD card.

Implement Hypervisor password policies.

Cisco Intersight Global Policy

Implement Hypervisor password policies.

Synchronize server power state.

Support tagging policies.

Cisco UCS Manager Local Policy

Scrub disks on disassociation.

Create a utility partition on a SD card.

NEW QUESTION 2

What influences the number of ISLs that are required between Cisco MDS Series switches?

- A. FCoE protocol
- B. type of storage
- C. end-to-end oversubscription ratio
- D. N Port virtualization

Answer: C

NEW QUESTION 3

Refer to the exhibit.

```
Switch(config-sys-qos)# show policy-map system
Type network-qos policy-maps
=====
policy-map type network-qos system
  class type network-qos class-fcoe
    match qos-group 1
    pause no-drop
    mtu 2000
  class type network-qos class-default
    match qos-group 0
    mtu 1500
Service-policy (qos) input: system
policy statistics status: disabled
Class-map (qos) : class fcoe (match-any)
  Match : cos 3
  set qos-group 1
Class-map (qos) : class-default (match-any)
  Match: any
  set qos-group 0
```

The FCoE packets fail to be forwarded through the switch. What is the minimum MTU QoS requirement for the FCoE to work?

- A. 9000 bytes
- B. 2000 bytes
- C. 2158 bytes
- D. 2240 bytes

**Answer:** B

#### NEW QUESTION 4

Which feature provides a sandbox to convert NX-OS CLI commands to REST-based scripts on Cisco Nexus 7700 Series Switches?

- A. NX-API
- B. Postman
- C. Bash shell
- D. Guest shell

**Answer:** A

#### NEW QUESTION 5

What is an advantage of Cisco HyperFlex Edge as compared to Cisco HyperFlex Standard Clusters?

- A. Cisco Intersight automatically creates an invisible cloud witness.
- B. Cisco UCS 5108 Blade Server chassis provides SEEPROM connectivity to solve split-brain scenarios.
- C. Cisco UCS Manager provides service profile portability across nodes.
- D. Cisco HyperFlex Edge provides native container support through the KVM hypervisor.

**Answer:** A

#### NEW QUESTION 6

Which two configuration methods can be used to deploy QoS to Cisco MDS Series switches? (Choose two.)

- A. zone-based QoS
- B. multiple QoS policies that match individual devices
- C. VSAN-based QoS
- D. FCoE VLAN-based QoS
- E. multiple QoS policies that match multiple devices

**Answer:** AC

#### NEW QUESTION 7

Which feature must be configured to connect a classical Ethernet network to a data center network so that the data center network appears to be one large switch.

- A. VPC+
- B. UDLD
- C. EVPN
- D. OSPF

**Answer:** C

#### NEW QUESTION 8

Drag and drop the feature descriptions from the left onto the correct UCS Fabric Interconnect modes on the right.

Links are active-active.	<b>End-Host Mode</b> <div></div> <div></div>
MAC address learning occurs on the uplink ports.	
STP runs on the uplink ports.	<b>Switch Mode</b> <div></div> <div></div>
This is the default mode of operation.	

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Links are active-active.	<b>End-Host Mode</b> <div>Links are active-active.</div> <div>MAC address learning occurs on the uplink ports.</div>
MAC address learning occurs on the uplink ports.	
STP runs on the uplink ports.	<b>Switch Mode</b> <div>STP runs on the uplink ports.</div> <div>This is the default mode of operation.</div>
This is the default mode of operation.	

#### NEW QUESTION 9

Which Ethernet to Cisco Fabric Interconnect connectivity configuration is supported when FCoE is implemented?

- A. VSS that has unified uplinks
- B. Ethernet and unified ports on the same port channel
- C. vPC that has unified uplinks
- D. cross-connections with pinning

**Answer:** C

#### NEW QUESTION 10

Which Cisco HyperFlex feature provides virtual machine-level cost scaling for desktop virtualization growth?

- A. HyperFlex Edge support
- B. encryption offload cards
- C. dedicated compute nodes
- D. fabric interconnects

**Answer:** A

#### NEW QUESTION 10


Which two automation requirements can be met by using Puppet? (Choose two.)

- A. Push configuration updates immediately to servers.
- B. Enable clients to pull changes to configuration files.
- C. Enable clients to pull changes without installing an agent.
- D. Provide support for writing new modules in Python.
- E. Enable one-off infrastructure changes to be performed manually.

**Answer:** AB



**NEW QUESTION 15**  
Refer to the exhibit.



A Cisco UCS chassis that has two IOMs is discovered. The chassis discovery policy creates a fabric port channel. What is the result of this policy?

- A. Cisco UCS Manager creates two separate fabric port channels.
- B. Cisco UCS Manager creates a single fabric port channel.
- C. The port channel is disabled until an administrator enables it manually.
- D. Each uplink that connects an IOM is configured as a discrete link.

**Answer:** A


**NEW QUESTION 16**  
Drag the appropriate from the left onto the current UDLD modes of operation on the right.

Uses STP if UDLD information times out.	<b>Normal Mode</b> <div></div> <div></div>
Detects when a port is stuck.	
Disables a port that has a high error rate.	<b>Aggressive Mode</b> <div></div> <div></div>
Allows a port that has a high error rate.	

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**



**NEW QUESTION 17**


When planning to deploy a load-balancing service as a managed node, which ACI configuration must be included?

- A. BGP ECMP
- B. Layer 4 to Layer 7 device package
- C. inline load-balancing device
- D. ITD

**Answer: B**

**NEW QUESTION 21**

Refer to the exhibit.



An engineer must assign multiple Fibre Channel IDs to a single port channel. Which two features must be enabled this goal? (Choose two.)

- A. SAN Pin Groups on the Cisco UCS Fabric Interconnects.
- B. NPV feature on the Cisco MDS Series.
- C. end-host mode feature on the Cisco UCS Fabric Interconnects
- D. NPIV feature on the Cisco MDS Series
- E. Smart Zoning feature on the Cisco UCS Fabric Interconnects

**Answer: BD**

**NEW QUESTION 26**

What is a design consideration when implementing FSPF?

- A. Routes are based on the domain ID.
- B. Routes are based on the distance vector protocol.
- C. FSPF runs only on F Ports.
- D. FSPF runs on a per-chassis basis.

**Answer:** A

#### **NEW QUESTION 31**

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### 300-610 Practice Exam Features:

- \* 300-610 Questions and Answers Updated Frequently
- \* 300-610 Practice Questions Verified by Expert Senior Certified Staff
- \* 300-610 Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* 300-610 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The 300-610 Practice Test Here](#)**